

LCMA

LM930



COMPACT WHEEL LOADER

Engine Power

65 kW / 87 HP

Bucket Capacity

0.90 m³

Operating Weight

4,500 kg

Rated Load

1,600 kg

LM930

Engine Power 65 kW / 87 HP	Bucket Capacity 0.90 m ³
Operating Weight 4,500 kg	Rated Load 1,600 kg

PERFORMANCE AND VERSATILITY

- Standard auxiliary hydraulics
- High departure angles
- Certified Cabin
- Complimentary Hydraulic Quick Hitch

OPERATOR CONFORT

- Prefect driver visibility
- Adjustable suspension seat
- Pilot proportional controls
- Easy to entry and egress
- Low noise
- Reverse camera

SERVICE AND MAINTENANCE

- Wide opening engine hood and side covers
- Side-by-side radiator and oil cooler are easily inspected
- Easy to access grease points
- Tilt-forward operator's station provides full access to engine and hydraulic components
- Coded hydraulic hoses making them easy to identify



AT A GLANCE

VALUE, DURABILITY AND STRENGTH

- Strongest center hinge
- Large diameter swing pin
- O-ring face seal hydraulic fittings
- Moisture/dust resistant electrical connectors
- Hydraulic lines are routed through boom for protection
- Optional side-open service access
- Optional emergency stop button



LM930

OPERATOR ENVIRONMENT



OPERATOR STATION

- Spacious canopy with unobstructed floor provides the operator with ample leg room
- Complimentary Hydraulic Quick Hitch
- Fully adjustable suspension seat reduces operator fatigue
- PPC controls are low effort and provide fine control
- Gauges and indicator lights are easy to read



COMPACT WHEEL LOADER

LM930

FEATURES



Strongest Center Hinge

The 3-layered center hinge is designed to withstand considerable horizontal and vertical stress. It can spread forces over a greater area for a long bearing life.



Counterweight Design

The sloped design of the counterweight can achieve very high departure angles, while its compact shape improves manoeuvrability in confined spaces.



Full view cabin

The cab with excellent visibility provides the driver with all-round visibility. Reversing camera, air conditioning and fan increase the driver's working comfort.



Hydraulic Quick Hitch

The standard hydraulic quick hitch of the whole series has two sets of hydraulic lines. By combining a variety of different attachments, you can increase your productivity and adapt to the work environment.

LM930

SPECIFICATION

ENGINE

Model	Huafeng 4102 diesel
Pattern	In-line, 4 cylinder
Rated power / speed	65 kW / 2,400
Weight	340 kg

ELECTRICAL SYSTEM

Operating voltage	24 V
-------------------	------

HYDRAULIC SYSTEM

Operating type	Hydraulic
Lifting time	5 s
Falling time	4 s

TRANSMISSION

Type	Hydraulic torque converter
Pattern	Automatic
Gear shift	Double H / L
Axle	AWD, small hub reduction

DRIVES AND BRAKES

Service brake	Air hydraulic disc brake
Parking brake	Hand brake

UNDERCARRIAGE

Tyre	16 / 70-16
------	------------

OPERATING WEIGHT (APPROX.)

Operating weight	4,500 kg
Rated load	1,600 kg

STANDARD AND OPTIONAL EQUIPMENT

Standard Equipment

- Hydraulic Quick Hitch
 - 4-in-1 Multi Purpose Bucket
 - General Purpose Bucket
 - Pallet Fork
-

Optional Equipment

- Bale Clamp
 - Drill Auger
 - Paddock Grapple
 - Sieve Bucket
 - Sweeper
 - Rotating Fork Rack
 - Light material bucket
-

MACHINE DIMENSIONS

Bucket capacity	0.90 m ³
Rated load	1,600 kg
Operating weight	4,500 kg
Overall dimension (mm)	5,500 x 1,850 x 2,760
Wheel base	2,250 mm
Wheel track	1,500 mm
Bucket width	1,900 mm
Max. dumping height	3,200 mm
Max. dumping distance	750 mm
Turning radius	4,900 mm

Product designs, specifications and/or data in this document are provided for informational purposes only and are not warranties of any kind. Product designs and/ or specifications may be changed at any time without notice. The only warranties that apply to sales of products and services are LGMA standard written warranties, which will be furnished upon request.

LGMA



lgma.com.au