



## Fagor EVO-CONCEPT glass washer with drain pump and detergent & rinse dispenser cold rinse CO-402BDD

### Quick Overview

E-VO CONCEPT glass washer with 350x350 mm basket (CO-352) and 400x400 mm basket (CO-402) with double wall rigid door. Dish service height up to 220 mm (CO-352) and 270 mm (CO-402). Constant water consumption of 2 litres per cycle for the rinse with a mains pressure of 2 bar.

- WaterMark approved

### Description

Fagor EVO-CONCEPT glass washer with drain pump and detergent & rinse dispenser cold rinse CO-402BDD

E-VO CONCEPT glass washer with 350x350 mm basket (CO-352) and 400x400 mm basket (CO-402) with double wall rigid door. Dish service height up to 220 mm (CO-352) and 270 mm (CO-402). Constant water consumption of 2 litres per cycle for the rinse with a mains pressure of 2 bar. New optimized hydraulic EFFI-WASH system, with stainless steel wash arms and 0.26 kW pump, guaranteeing a top quality effective, and efficient wash with an optimum Sinner circle balance. It also has a built-in rinse aid dispenser drainage pump (B) and detergent dispenser (DD) fitted at the factory or supplied in kit form. It has adjustable feet to permit leveling according to the needs of the establishment. Magnetic door open sensor. Electronical control panel making it easy to use.

## Key Features

- Front loading glasswasher - EVO Generation - Advanced range.
- Basket size: 400 x 400 mm.
- Hourly production: 40 baskets/hour.
- Clearance (max ware height): 275 mm.
- Valid for dishes Ø 270 mm.
- Wash cycles: 90" - 120" - 180".
- Electronic control. Digital displays.
- Selector for an optional cold rinse at the end of the cycle.
- Made of stainless steel.
- The door has double skin.
- Double rotating wash and rinse systems, above and below, made of stainless steel.
- Wash pump: 260 W.
- Drain pump: 30 W. Drainage cycle.
- Tank with 2.0 kW heating element.
- Tank capacity: 13 litres.
- Boiler with 2.8 kW heating element.
- Boiler capacity: 4 litres.
- Water consumption: 2.4 litres/rinse.
- Thermostatic temperature control: washing at 60 °C and rinsing at 90 °C.
- Security thermostats.
- Built-in automatic rinse dispenser and detergent doser.
- Built-in non-return valve.
- Safety magnetic switch for door opening.
- Adjustable legs.
- WaterMark approved

## Additional Information

- Total power: 3.06 kW.
- Dimensions: 470 x 520 x 720 mm.
- Equipment: one basket 400x400, one supplement for dishes and one cutlery container.

2 Years Parts and Labour Warranty

## Your Shipping Specifications

---

Net Weight (Kg)	36
Width (mm)	470
Depth (mm)	520
Height (mm)	720
Packing Width (mm)	530
Packing Depth (mm)	680
Packing Height (mm)	890
Power	11.02 MJ
Warranty	2 Years Parts and Labour