P3

Effective 11th May 2018

Replaces all previous versions

WANA FRACYFIT CORA ALL

AW Series Electric Shuttle Bus 8 Seats with Doors

This fully fitted, Environmentally friendly Bus design allows comfortable transport for Resorts, Parks, Commercial Developments, Schools and Staff transport at building sites.



SPACEPAC EM®VEIT





* Images shown - Non Standard Colours





STANDARD FEATURES INCLUDE:

- Automotive windshield.
- American original CURTIS electronic control, imported electronic control, quality assurance.
- · Military quality battery for durability.
- LED lights.
- 48V 5 KW AC Electric motor
- 3 Point seat Belts, Internal Mirror, twin external mirrors
- CD, Radio, Speakers, Microphone for public address
- Right Hand Drive (optional LH Drive)
- Power Steering, Floor Mat
- Front Disk & Drum Rear Brakes with Vacuum Booster
- Optional Solar panel for charging the batteries.
- Conditional registration, site specific suitable for this vehicle.

WARRANTY:

2 Years Machine & accessories 12 month on batteries

STANDARD COLOURS - OTHER COLOURS (POA)

White	Pearl White	Pearl Red	Greece Yellow	Lake Green	Black
-------	----------------	--------------	------------------	---------------	-------

All prices/specifications subject to change without notice.

Add 10%GST Australia only

PO Box 1468 Auburn St. Wollongong NSW 2500 Ph: 1300 213 010 Email: sales@emoveit.com.au

WWW.EMOVEIT.COM.AU

P3

Replaces all previous versions

Effective 11th May 2018

AW Series Electric Shuttle Bus 8 Seats with Doors

Nodel		# AW6082KF01	# AW6082KF04			
Please er	mail to sales@spac	cepac.com.au for more information	n and recent pricing			
lectric system						
System voltage		48V, series	48V, AC			
Motor		5KW motor, DC	5KW motor, AC			
Battery (top quality lead-acid)		8 X 6V (210AH)	8 X 6V (210AH)			
Controller		Curtis 1205M	Curtis 1232SE			
echnical Specifications		03.33 1200	56.65 2252			
Passenger capacity		8	8			
Range - loaded (flat road at20km/h)		>65 KM >65 KM				
Max. speed		28 KM/H	30 KM/H			
Max. climbing ability (loaded)		15%	20%			
Min.turning radius (m)		4.5m	4.5m			
Max. movement after brake at speed of 20km/h		≤ 4 m	≤ 4 m			
Max. loading weight		640 kgs	640 kgs			
Overall dimensions (mm)		4100 x 1535 x 2070	4100 x 1535 x 2070			
ody and Frame						
Frame	Welded steel fram	ework with sand blasting + paint treatme	ent			
Body	Steel frame + fiberglass					
Roof	Fibreglass + aluminum frame, with roof handle					
Door	Aluminum structure + tempered glass					
Windshield	Laminated glass					
Seats	High quality of artificial leather with 3 Point Seat Belt					
Floor	Non-slip floormat					
Inner rear view mirror	One piece per cart in the middle of the windshield					
Side rear view mirror	Two pieces per cart					
Colour (standard)	White, Pearl White, Pearl Red, Greece Yellow, Lake Green, Black Brown (seat)					
lectric system	,	, , , , , , , , , , , , , , , , , , , ,				
•	Front: 2 Headlights (High beam and dipped headlight), 2 front turn signals, 2 fog lights;					
Lighting system and horn	Back: 2 rear turn signals, 2 taillights(position light & brake light), 1 fog light, 1 reverse light), with DC-l					
6	converter (converting)					
	Combination instrument including power consumption, voltage, current, speed, mileage, time, light,					
Instruments on dashboard	F/R switch, and signal.					
	<u> </u>					
Audio System	CD and Radio, speakers, Microphone					
Switch assembly	Combination switch including Power key, Light and wiper combination switch, F/R switch and reverse					
Switch assembly	buzzer switch					
Solar panel	OPTIONAL: For charging the batteries					
Charger	non-onboard OR onboard					
teering and Suspension						
Steering system	Rack and pinion drive					
Electrical power steering	Included					
Brake system	Front disc brake and rear drum brake, with vacuum booster					
Transmission system	Automatic drive system (stepless speed change)					
Front suspension	Independent suspension					
Rear suspension	Integral rear axle, coil spring non-independent suspension, hydraulic shock absorber tube					
Wheel & Tyre	4J*12 Aluminum wheel, wheel cap, 155R12,8PR					

All prices/specifications subject to change without notice.

Add 10%GST Australia only