



Application

- Power Stations
- Marine Industries
- Petrol Stations
- Petrochemical Industries
- Railway Stations
- Large Workshops
- Disaster Relief
- Industrial Areas

Electrical Parameters

MODEL (ETG)	ETG-EXHERO350	ETG-EXHERO400	ETG-EXHERO440	ETG-EXHERO480
Rated power	350W	400W	440W	480W
Luminous flux (lm)	42,000	48,000	52,800	57,600
Input Voltage	AC 220-270V			
LED Source	Cree / Philip			
Driver	Meanwell			
Beam Angle	90°			
CCT	3000 - 6500K			
CRI	Ra>75			
Luminous Efficacy (lm/W)	120			
IP / Anti-Corrosion Rating	IP66/WF2			
PF	>0.95			
Operating Temp	-30 ~ 50°C			
Dimensions (LWH)	425 x 195 x 630 mm			
Weight	28kg			
Lifespan	100,000 Hours			
Warranty	5 Years			

Ex HERO AREA FLOOD LIGHT

- + High powered flood light ideal for hazardous areas
- + Anti corrosion and water/dust proof to IP66
- + Excellent heat dissipation performance
- + Short circuit and over-voltage protection
- + Stylish, slimline design
- + High efficacy lighting at 120 lm/w

Certifications & Ratings

- + Ex d e mb IIC T5
ATEX, IECEx, CE, RoHS, IP66

