



PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PRINCETEL, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PRINCETEL, INC. IS PROHIBITED.

STANDARD SPECIFICATIONS	
PARAMETERS	VALUES
Wavelength range	850 nm
Insertion loss	<4 dB/channel 1, <6 dB/channel 2
Insertion loss WOW	<+/-1 dB
Return loss	~15 dB
Crosstalk	>50 dB
Maximum speed	100 rpm
Estimated life cycle	100-200 million revolutions
Working temperature	-40 to 72 C
Storage temperature	-45 to 75 C
Package style	Pigtails on both ends
Housing material	Stainless steel
Fiber types	MM, GI 62.5/125/900um
Jacket types	900um on rotor, 3 mm on stator
Connector types	Rotor: 1.25mm ferrule only ; Stator: FC/PC
Vibration	MIL-STD-167-1A
Mechanical shock	MIL-STD-810G
IP rating	IP 60

UNLESS OTHERWISE SPECIFIED:
 DIMENSIONS ARE IN mm
 DO NOT SCALE DRAWING

TOLERANCES:
 ANGULAR: $\pm 1/2^\circ$
 ONE PLACE DECIMAL ± 0.100
 TWO PLACE DECIMAL ± 0.050
 THREE PLACE DECIMAL ± 0.025

MATERIAL:

DRAWN	DATE	NAME	PRINCETEL, INC. TITLE: MJ2, FORJ
CHECKED	11/27/2017	L. X.	
ENG APPR.			
MFG APPR.			
Q.A.			
COMMENTS: FIRST ANGLE PROJECTION			SIZE DWG. NO. REV B 102-RMA2028 1
			PART NO. SHEET 1 OF 1 MJ2-850-62TK-0007-0060-12FC