

KT3 order picking trolley

The all-round talent

> System design with individual structure

> Load capacity up to 300 kg















KT3 basic model with accessories
Dimension (mm): L 900 x W 460 x H 1,630

Standard equipment: Chassis made of square tubing with welded bottom tray. Side panels made of square tube frame with wire grate, inserted into chassis and screwed into place. Shelves can be screwed in at height increments of 100 mm.

Castors: 4 Wanzl swivel castors, Ø 125 mm, rubber tread. Optional: 5th castor Ø 125 mm, fitted in the centre for easy manoeuvrability. The order picking trolley can turn on the spot.

Finish: 1. Zinc plating + transparent powder coating.
2. Color powder coating.
3. Zinc plating.

	KT3 with length of 900 mm	
		
		
Forklift loops for the KT3 with a length of 1,297 mm and 1,713 mm		
		
Basic model order no.	06.00 230.52 / 73 / 50	06.00 232.52 / 73 / 50
A, length (mm)	900	900
B, width (mm)	467	625
C, height (mm)	1,630	1,630
D, Plat form length (mm)	850	850
Load capacity per shelf (kg)	75	75
Total load: with real panel / without real panel (kg)	200 / 100	200 / 100
Structural elements		
 Rear panel grate Screwed on, mesh size 50 x 50 mm	00.52 812.50	00.52 812.50
Static elements [Ⓢ]		
 Wire shelf, screw-on Mesh size 100 x 30 mm	00.05 372.50	00.69 634.50
Shelves		
 Wire shelf, attachable Mesh size 100 x 30 mm	00.14 299.50	00.15 994.50 (on request)
 Wire shelf, attachable Mesh size 100 x 30 mm, with raised edge of 100 mm on both sides	00.39 159.50 (on request)	00.41 193.50
Accessories		
 Pushing handle (pair) made of plastic-coated steel tubing in RAL 5002 ultramarine blue or RAL 3000 flame red	00.40 570.76	00.40 570.76
 Writing board Coated metal board with deep black surface	00.54 979.95	00.54 979.95
 Wire tray for small items Plastic-coated in RAL 9005 jet black	00.14 378.76	00.14 378.76
 5th castor Mechanical, Ø 125 mm	60.01 017.50	60.01 017.50
 Ladder Folding, 3 levels with non-slip chequered rubber surface	00.84 409.50	00.07 106.50

Other accessories available on request.

[Ⓢ]A static element must be used with loads of 50 kg or more or when using a ladder.