



SERVICE LIFTS AND DUMB WAITERS



Australia's largest independent lift company
Established 1985

**Quick and easy to install in new and existing buildings.
Simple user-friendly operation. Low energy consumption.**

Liftronic's range of Service Lifts and Dumb Waiters are the proven solution for the needs of commercial and domestic applications.

Designed for reliability the eco-friendly lifts are available in pre-engineered configurations that can be customised to suit specific dimensions and specifications.

Features include

- From 50kg – 1000kg
- Call and send operation
- Position indicator
- Arrival buzzer and call signal
- Supporting structures available
- Available with/without passenger transport
- Quick and easy installation
- Ideal for existing buildings
- Compliant with Australian Standards/BCA




Visit our website to discover our comprehensive range of elevators, escalators and moving walkways. www.liftronic.com.au





Type	Capacity	Door Height (DH)	Speed	Cabin Dimensions (Variable In 25 mm Increments)		Shaft Dimensions		Pit Depth / Serving Height (mm)	Min Headroom (mm)
				Width	Depth	Width	Depth		
ISO-A Vertical bi-parting doors on serving height	50kg	600 - 1200 mm	0.4 m/s	400 - 600	400 - 600	cabin width + 300	cabin depth + 150	Sh=min 700	servicing height + door height + 1260
	100kg	600 - 1200 mm	0.4 m/s	400 - 1000	400 - 1000	cabin width + 300	cabin depth + 150	Sh=min 700	servicing height + door height + 1260
	300kg	600 - 1200 mm	0.25 m/s	400 - 1000	400 - 1000	cabin width + 300	cabin depth + 150	Sh=min 700	servicing height + door height + 1360
ISO-C Vertical bi-parting doors serving at floor level	100kg	600 - 1200 mm	0.27 m/s	500 - 1000	500 - 1000	cabin width + 350	cabin depth + 150	P=min DH / 2 + 50	door height + 1260
	300kg	600 - 1200 mm	0.25 m/s	500 - 1000	600 - 1000	cabin width + 350	cabin depth + 150	P=min DH / 2 + 50	door height + 1360
ISO-D Swing doors serving at floor level	100kg	600 - 1200 mm	0.27 m/s	400 - 1000	500 - 1000	cabin width + 350	cabin depth + 110	P=min 350	door height + 1260
	300kg	600 - 1200 mm	0.25 m/s	400 - 1000	600 - 1000	cabin width + 350	cabin depth + 110	P=min 350	door height + 1360
ISO-MAX Goods lift with out passenger transport	300kg	1200-2000 mm	0.15-0.25 m/s	800 - 1000mm	1100 - 1500mm	Cabin width +400mm	Cabin Depth +110mm	275	door height + 1300
	500kg			1000mm or 1275mm	1400mm or 1500mm	Cabin width +475mm	Cabin Depth +165mm	200	
	1000kg								
ISO-PE Goods lift with passenger transport	750kg 1000kg	2000-2200 mm	0.15-0.25 m/s	800 - 1500mm	1100 - 1800mm	Cabin width +475mm	Cabin Depth +165mm	200	door height + 1000



Australia's largest independent lift company
Established 1985

BRISBANE

29 Canberra Street
HEMMANT
QLD 4174
PO Box 7107
HEMMANT QLD 4174
Tel: +(61 7) 3890 0522
Fax: +(61 7) 3890 0722

MELBOURNE

640 Somerville Road
SUNSHINE WEST
VIC 3020
PO Box 1195, ALTONA
GATE VIC 3025
Tel: +(61 3) 9311 6663
Fax: +(61 3) 9312 6663

CANBERRA

L11 St George Cntr
60 Marcus Clarke St
ACT 2600
PO Box 1195, ALTONA
GATE VIC 3025
Tel: +(61 2) 6243 4844
Fax: +(61 2) 6243 4845

SYDNEY

Unit 6 153 Beauchamp Road
MATRAVILLE
NSW 2036
PO Box 75
BOTANY NSW 1455
Tel: +(61 2) 9666 3922
Fax: +(61 2) 9666 4507