







EXPRESS STACK WASHER-DRYER

Dexter C-Series Powered by DexterLive Controls

Vended laundry solutions you can depend on.

Dexter C-Series vended stack washer-dryers are engineered to show up for work in even the harshest laundry environments. Featuring DexterLive controls, next generation components, and high quality materials, these space saving combination units are designed to help make you more successful.

A store full of laundry equipment is a big investment and choosing the right equipment is an important decision. Our products will provide you the efficiency, flexibility, performance, and durability you need to be confident in your choice. With lifetime technical support and an industry leading warranty, you can be confident that we will stand behind every stack washer-dryer you invest in.

Contact your Dexter Authorized Distributor today for more details.

DURABLE:

With heavy-duty bearings in cast iron bearing housings, welded steel spiders and shafts, and rugged frame and cabinet designs, Dexter stack washer-dryers are built to last.

The washer design has been tested thoroughly with our 1,000 hour out-of-balance test.

The polished chrome doors and AISI 304 stainless steel tub, cylinder, and panels keep machines looking great for years.

RELIABLE:

We offer an industry leading 10 year limited warranty on the washer unit and a 5 year limited warranty on the dryer.

A 3 year parts warranty covers the rest.

We stand behind every machine you invest in with lifetime technical support.

EFFICIENT:

With a dry-to-dry time of less than one hour, the Dexter stack washer-dryer works fast and efficiently.

A next generation inverter drive on the washer lowers electrical usage, improves performance, and extends the life of motor.

Powerful Express 200 g-force extraction removes more water to reduce dry time and helps save of energy costs.

INSTALLATION:

This combination unit provides a full laundry solution in a single footprint and is ideal for laundries with limited space.

The adjustable final extract speed allows the unit to fit almost any location.

This Dexter washer fits through a standard 36" door way.

PROFITABLE:

Every Dexter machine is now easier to use with a common user interface on all products, multiple language options, and detailed customer prompts.

DexterLive controls work with DexterLive.com to allow you to create custom programs that fit your business.

A variety of PLUS cycle features and promotion options will help you maximize revenue generation.

OPTIONS:

Available with blue or black graphics, stainless steel or galvanized dryer tumblers, and chrome or stainless steel dryer doors.

Your machines can be shipped with coin acceptors or payment system ready.

Gas models, with propane kits available.

EMPLOYEE OWNED | MADE IN THE USA | SINCE 1894

EXPRESS STACK WASHER / DRYER SPECIFICATIONS

OVERALL SPECIFICATIONS:

0----

Capacity: Dry Weight Capacity (per machine) Washer Cylinder Volume Dryer Cylinder Volume	30 lb 4 cu ft 11.3 cu ft	(13.6 kg) (113.3 L) (320 L)
Speed: Washer High Extract Speed Washer Intermediate Extract Speed Washer Washing Speed Washer Motor Size Dryer Tumbler Speed Dryer Motor Size	200 g 60 g 0.9 g 2 hp 47 RPM 0.5 hp	(750 RPM) (411 RPM) (50 RPM) (1.5 kW)
Airflow (Dryer Only): 60 Hz Model 50 Hz Model	500 cfm 450 cfm	(14.6 M3/min) (12.7 M3/min)
Dimensions: Overall Height Overall Width Overall Depth	78 3/4" 31 1/2" 47 5/16"	(200 cm) (80 cm) (120.2 cm)
Washer Cylinder Diameter Washer Cylinder Depth Washer Door Opening Floor to Washer Door Bottom	25" 14 1/8" 15 1/4" 12 7/16"	(63.5 cm) (35.9 cm) (38.7 cm) (31.6 cm)
Dryer Cylinder Diameter Dryer Cylinder Depth Dryer Door Opening Floor to Dryer Door Bottom Dryer Lint Screen Area	30" 27 1/2" 22 11/16" 46 15/16" 453 sq in	(76.2 cm) (69.9 cm) (57.6 cm) (119.2 cm) (2923 sq cm)
Weight: Net Weight	1039 lbs	(471.3 kg)
Shipping Information: Shipping Weight Shipping Height Shipping Width Shipping Depth	1090 lbs 83 1/4" 33" 54"	(494.4 kg) (211.5 cm) (83.8 cm) (137.2 cm)
Installation Recommendations: Minimum Clearance Between Machines Minimum Clearance Behind Machines Minimum Concrete Thickness Make-Up Air Required Exhaust Size	1/2" 24" 6" 1 sq ft 6"	(1.3 cm) (61 cm) (15.2 cm) (929 sq cm) (15.2 cm)

WASHER REQUIREMENTS:

Water Requirements:		
Water Inlet Size	3/4"	(19 mm)
Flow Rate (per min)	9 gal	(34.1 L)
Pressure (min/max)	30-120 psi	(207-827 kPa)
Approximate Water Usage (per cycle)	32 gal	(121.1 L)
Maximum Hot Water Usage (per cycle)	22.7 gal	(85.9 L)
Drain Diameter (O.D.)	3"	(7.6 cm)
Floor to Center of Drain	4 7/16"	(11.3 cm)

Electrical Requirements:

Model	Volts / Hz / Phase / Wiring	Circuit Breaker / Running Amps / Wire Size
-12	208-240 / 60 / 1 / 2 wire + ground	15 amp / 6.2 amp / #12
-12	208-240 / 60 / 3 / 3 wire + ground	15 amp / 6.2 amp / #12
-39	230 / 50 / 1 / 2 wire + ground	15 amp / 6.2 amp / 3.5 mm ²

DRYER REQUIREMENTS:

_	ь .				
Gas	Reaui	remen	its (Gas	Models	Only):

Gas Supply Connection	1/2"	(12.7 mm)
Natural Gas Supply (Water Column)	5-10"	(12.7 - 25.4 cm)
LP Gas Supply (Water Column)	11 1/2 - 14"	(29.2 - 35.5 cm)

Gas Usage (Gas Models Only):

60Hz Model	80,000 BTU/hr	(23.4 kW)
50Hz Model	74 000 BTU/hr	(21.7 kW)

Electrical Requirements:

Gas Models:

Model	Volts / Hz / Phase / Wiring	Circuit Breaker / Running Amps / Wire Size
-10	120 / 60 / 1 / 2 wire + ground	15 amp / 9.8 amp / #12
-39	230 / 50 / 1 / 2 wire + ground	15 amp / 5 amp / 3.5 mm ²

Liectric	Wodels.	
Model	kW / Volts / Hz / Phase / Wiring	Circuit Breaker / Running Amps / Wire Size
-79	24 / 400 / 50 / 3 / 4 wire + ground	50 amp / 45 amp / 13.3 mm ²

AGENCY APPROVALS*





