Tenso[®] TS-600

Fully - Automatic Strapping Machine

#60331



EasySimpleAdjustableTough SteelOperationMaintenanceTensionConstruction





The Fully Automatic Strapping Machine TS-600, is a high-quality machine that combines ease of operation and maintenance, with high value at an economical price.

This efficient machine uses polypropylene strap width s ranging from 8mm to 15.5mm, can tension straps from 10 to 70kg, operates at up to 27 straps per minute, and is the most cost-effective solution for wide straps in general applications.

Features

- Operates at up to 27 straps per minute
- Adjustable Strap Width: 8 mm to 15.5 mm
- High performance machine for high volume strapping
 users
- Adjustable tension with an external dial
- Reliable and Easy Operation: Ensures dependable and user-friendly performance
- Operational flexibility: Choose auto or manual strapping
- Foot-Pedal Control

Specifications

High-Performance Strapping

specifications	
Sealing Method	heat
Speed /minute	27 Straps
Strap Width	8 mm to 15.5 mm (3/8"- 5/8")
Strap Thickness	0.55 mm up to 0.75 mm (0.022 - 0.03")
Strap Reel Diameter	200 mm (8" nominal)
Strap Tension	10 - 70kg
Width	1430 mm (56.3")
Depth	620 mm (24.4")
Table Height	810 mm (31.9")
Arch Size	850mm(W) x 600mm(H)
Power	AC 110V/220V/230V/240V (50/60Hz), 1Phase AC 220V/380V/400V (50/60Hz), 3 Phase
Weight	220 kg (341.7 lbs.)
Noise Emission	83 dB (A)
Ambient Temp	5° ~ 40° (41° ~104°)

