GH7000-3



GH7000-3



PORTABLE POWER



Technical

| Model |
|------------------------|
| Туре |
| Speed |
| Phase/Voltage |
| Frequency |
| Max power kW |
| Continuous Output |
| Noise Level (dBA @ 7m) |
| Frame |
| |

GH 7000-3 Portable 3000 RPM 3/415 50 Hz 7.0kW 8.0kVA 77 Extra Large Roll Frame

Engine

Manufacturer Engine Model Type Starting Fuel Run Time Tank Capacity HP 3000 rpm cont Cubic Capacity Oil Capacity Honda GX390 O.H.V. Recoil & Electric Start Unleaded Petrol 2.6 hr @ 100%, 3.8hrs @60% 6.1 L 8.0 HP 389 cm³ 1.1 L

Alternator

Alternator Brand Type Harmonic Distortion Protection Class Insulation Class Mecc Alte Brushless Less than 5% IP 23 Class H

Outlets

Outlet

1 x 10amp 5 Pin IP66 3 Phase with Thermal Overload Protection 2 x 15amp 3 Pin Single Phase with Thermal Overload Protection

Dimensions & Weight

| Length | 85 cm |
|--------|-------|
| Width | 57 cm |
| Height | 60 cm |
| Weight | 80 kg |

Options

Outlets Protection Wheel kits Frames Alternators Long Range Tank

Weather protected IP33 & Weatherproof IP66 RCD/ELCB IP30 or IP66 Two Wheel or Four Wheel Extra Large Roll Frames Oversized, Single or Three Phase 15 Litre Capacity

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.