MLG32PD

MAYTAG® COMMERCIAL ENERGY ADVANTAGE™ MULTI-LOAD STACK DRYER





LEGENDARY MAYTAG DEPENDABILITY

Maximizing your equipment investment for over a half century.



MORE ENERGY-SAVING SOLUTIONS THAN ANY OTHER BRAND

Maytag built the first appliance ever to receive the ENERGY STAR® label. Today we offer more high-efficiency laundry appliances than any other brand—from energy-efficient dryers to highly efficient ENERGY STAR®-qualified washers—to help you save money and build profits.

FOR YOUR CUSTOMERS:

- Fast-Drying Axial Airflow System
- ThermoGuard™ System Helps Prevent Laundry Overheating
- Extra-Large Door Openings
- Time Remaining Digital Display
- Microprocessor Controls

FOR YOUR OPERATION:

- Lowest-BTU Dryer On The Market
- Improved Insulation For Greater Efficiency
- Front Serviceable
- Single Coin Box For Both Dryers
- Front Access For Easier Self Service
- 2 Large-Capacity Lint Drawers

S.A.F.E. SYSTEM:

• Sensor-Activated Fire Extinguishing System

BUILT-TO-LAST™ FEATURES:

- Maytag® Exclusive S.A.F.E. Extinguishing System
- Heavy-Duty Enclosed Motors
- 5-Year Limited Warranty—All Parts Covered





Shown in Stainless Steel.

LAUNDRY SOLUTIONS
YOU CAN DEPEND ON.

SAVES UP TO 25% IN ENERGY AND UTILITY COSTS*



OUR COMMITMENT TO DEPENDABLE QUALITY

At Maytag, we believe durable goods should remain just that. That's why every Maytag® product is constructed of the highest-quality materials and with the utmost in precision craftsmanship. It's also why we stand behind our equipment with solid service and support from our professional Maytag laundry suppliers. Simply put, when you choose Maytag® products, you ensure your peace of mind.




MLG32PD **MAYTAG® COMMERCIAL ENERGY ADVANTAGE™ MULTI-LOAD STACK DRYER**


Maytag[®] Commercial Energy Advantage[™] **Multi-Load Stack Dryer**


MICROPROCESSOR COIN-DROP


DRYER SPECIFICATIONS	
MODEL	MLG32PD
MOTOR	
Single-phase, thermoprotected against overload, auto-reset	•
Drive Motor — HP (kw)	.25 (.19)
Blower Motor — HP (kw)	.50 (.37)
CAPACITY	
Lbs. (kg) per drying chamber	2-30 (2-13.6)
Cu. ft. (cu. m) per drying chamber	2-11.04 (2312)
AIRFLOW	
Cfm (cmm) per drying chamber	360 (10.2)
TUMBLERS	
Diameter — mm	2-762
Depth — mm	2-685
DOOR OPENING DIAMETER	
mm	492
ELECTRICAL REQUIREMENTS	
Voltage	220-240V/1PH
BREAKER/FUSE REQUIREMENTS	
Amps per drying chamber	8
EXHAUST DUCT DIAMETER	
mm	152
GAS RATING	
BTU/hr. (kcal/hr.) per drying chamber	55,000 (13,860)
GAS INLET	
M.N.P.T. mm	2 inlets, 12.7
COLORS	
Stainless Steel	•
APPROXIMATE WEIGHT	
Crated — kg	263
Uncrated — kg	249
DIMENSIONS	
Height — mm	2042
Width — mm	791
Depth — mm	887
Door opening diameter — mm	492
See specific instructions for proper installation.	



Because of continuous product improvement, Maytag reserves the right to change specifications without notice.













5-YEAR LIMITED WARRANTY ALL PARTS COVERED

For a period from the date of original purchase through the time listed above, the designated parts that fail in normal commercial use will be repaired or replaced free of charge for the part itself, with the owner paying all other costs, including labor, transportation and customs duty. Chemical damage is excluded from all warranty coverage. See complete warranty for details.

