



Class 4 Dangerous Goods Cabinets

Pratt Indoor Class 4 Storage Cabinets comply with the new Standard AS/NZS 5026 "The Storage and Handling of Class 4 Dangerous Goods".

This range of cabinets is for the storage of Class 4 chemicals in liquid or solid form as classified by the United Nations criteria and the ADG Code for Dangerous Goods. Please refer to the Standard.

These include the following divisions:

- Flammable Solids
- Spontaneously Combustible
- Dangerous When Wet

Special Features:

- ▲ Cabinets are fitted with a non latching door/s.
- ▲ Includes recessed handle without key lock facility.
- ▲ Includes magnetic catch that will release in the event of a build-up of pressure within the cabinet (as required by this Standard).



New Range of Storage Cabinets

Model	Capacity	Doors	Shelves	Extra Shelf	External (mm)			Internal (mm)		
					Height	Width	Depth	Height	Width	Depth
5516AC4	30kg or L*	1	1	5517-29	770	515	465	525	420	370
5517AC4	60kg or L*	1	2	5517-29	1065	515	465	820	420	370
5535AC4	100kg or L*	2	1	5535-29	770	935	620	495	840	530
5530AC4	160kg or L*	2	2	5545-29	1295	1115	500	1015	1020	415
5545AC4	250kg or L*	2	3	5545-29	1825	1115	500	1545	1020	415

* AS/NZS 5026 specifies a maximum of 25kg or L for Category A, 50kg or L of Category B or 100kg or L of Category C, Class 4 Chemicals. Other capacity limitations do apply. Refer to the Standard for further details.

Note: 1. For all two door cabinets, the internal height taken from top of sump sill to the sequential chassis assembly.

2. For all single door cabinets, the internal height is taken from the top of the sump sill to the ceiling.

3. For total external width measurement, add 6mm per vent bung for tight clearance locations.