

CLEANING MACHINES FOR UNCLASSIFIED (GENERAL PURPOSE) AREAS

All the electrical components are certified by an NRTL such as UL, CSA or ETL



### Characteristics



Continuous  
Duty



Wet and Dry  
Recovery



Detachable  
Tank



SS 430



HEPA Filter  
Available

HEPA - Optional

- Low cost vacuum system for continuous duty
- Available in Single or 3-phase configurations
- Regenerative blower with TEFC induction motor rated for continuous duty
- Very powerful machine
- Main filter with Manual Filter Shaker (MFS)
- Upstream filter cartridge for fine dust
- HEPA Filter with a minimum efficiency of 99.97% at 0.3 micron (installed in the place of the upstream filter cartridge) - optional
- Stainless steel SAE 430 filter chamber and recovery tank
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Standard configuration is for dry recovery only. Optional floater (liquid cut-off) is available for liquid recovery. Floater is installed in the place of the cyclonic separator
- Basic tool kit included

## Specifications

PLANET 115M GL	111208A1	111208A2	111208A4
<b>Model Name</b>	PLANET 115M GL	PLANET 115M GL	PLANET 115M GL
<b>Type (Powerhead)</b>	Electric	Electric	Electric
<b>TEFC Motor</b>	Yes	Yes	No
<b>Voltage</b>	460 V	230 V	230 V
<b>Hertz</b>	60 Hz	60 Hz	60 Hz
<b>Phase</b>	Three	Three	Single
<b>Wattage</b>	1500 W	1500 W	1500 W
<b>Power</b>	2 HP	2 HP	2 HP
<b>Air Flow</b>	118 CFM	118 CFM	118 CFM
<b>Vacuum Pressure</b>	80 " H <sub>2</sub> O	80 " H <sub>2</sub> O	80 " H <sub>2</sub> O
<b>Sound Level</b>	73 dB(A)	73 dB(A)	73 dB(A)
<b>Plug Type</b>	Not Included	Not Included	Not Included
<b>Suction Inlet</b>	60 mm	60 mm	60 mm
<b>Cart Type</b>	Detachable Tank (DT)	Detachable Tank (DT)	Detachable Tank (DT)
<b>Filter Cleaning</b>	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)
<b>Filter Type</b>	HEPA H14	HEPA H14	HEPA H14
<b>Filter Surface Area</b>	15 ft <sup>2</sup>	15 ft <sup>2</sup>	15 ft <sup>2</sup>
<b>Dry Recovery - Tank</b>	15.6 Gal	15.6 Gal	15.6 Gal
<b>Liquid Recovery Capacity</b>	15.6 gal.	15.6 gal.	15.6 gal.
<b>Filter Efficiency</b>	99.97	99.97	99.97
<b>Particle Size</b>	0.3	0.3	0.3
<b>Weight (Vacuum Only)</b>	160 lb.	160 lb.	160 lb.
<b>Cord Length</b>	30 ft.	30 ft.	30 ft.
<b>Container Material</b>	430 Stainless Steel	430 Stainless Steel	430 Stainless Steel
<b>Container Diameter</b>	16.5 "	16.5 "	16.5 "

Please note that specifications are subject to change without notice

## Use only recommended tools & accessories




Detachable Exhaust Silencer (GL Series)



Floater (Liquid Cut-Off) (GL Series) - Optional



Side view of Detachable Tank (GL Series)



Filter Cartridge (GL Series)



Polyester Main Filter (GL Series)



Suction Inlet, 60mm, Aluminum (GL Series)



Top Mounted Filter Shaker (GL Series)



Basic Tool Kit (GL Series) - Included



Cyclonic Separator (GL Series) - Included