

SCG15S3

Silent Type

Powered By Perkins



CONFIGURATION:

Standard: Engine, alternator, cooling system, Base frame, shock absorber, air system, control box, plastic fan blades (when the engine and water tank do not bring).


Optional: Water jacket heater, oil preheater, anti-condensation heater, fuel water separator, fuel heater, fuel level sensor, water level sensor, automatic fueling system (only supporting base frame including fuel tank).

Accessories: Silencer, bellow, exhaust silencing system accessories (with the matching engine), regular battery, data of generators, random tool (with the matching engine).

FETURES

- >> Powered by Perkins engine with reliable power output
- >> Easy maintenance and operation
- >> Compact design
- >> With forklift pockets and lift point for transportation
- >> Suitable for all weather conditions

Basic Information



Engine		Perkins 403A-15G
Alternator		Stamford PI044G
Controller		Smartgen HGM6120
Prime Power	KVA/KW	15/12
Standby Power	KVA/KW	16.5/13.2
Rated Speed	RPM	1500
Rated Frequency	HZ	50
Rated Voltage	V	415/240
Phase		3
Power Factor		0.8
Governer method		Mechanical
Rated Current	A	20.9
Fuel Consumption @ 100% Load	L/H	4.9
Dimmension	LxWxH mm	2260*948*1563
Dry Weight	Kg	960
Fuel Tank Size	L	210
Noise Level @ 7 meters	dBA	72

Note:

- (1) **Prime Power:** Prime power is available for an unlimited number of annual opearting hours in variable load applications; in accordance with ISO8528-1. A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation, in accordance with ISO3046-1.
- (2) **Standby Power:** Standby power is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.
- (3) The following voltages can be customized on requirement: single phase - 220V/230V/240V; three phase - 380/220V, 400/230V, 415/240V, 440/254V.
- (4) We reserve the right to modify the specifications without prior notice. All ratings are for guidance only, please refer to the final specific generator information from us.

SCG15S3

Silent Type
Powered By Perkins

Engine Specification

Model	403A-15G
Manufacturer	Perkins
Number of cylinders	3
Cylinder arrangement	Vertical In-line
Cycle	Four stroke
Induction system	Naturally aspirated
Compression ratio	22.5:01
Bore x Stroke	84x90 mm
Displacement L	1.496
Estimated total weight (dry) kg	197
Rated power at 1500rpm KW/HP	13.3/18
Lubrication oil capacity L	6
Coolant capacity L	6
Governor method	Mechanical
Starting system	Electric
Type of injection model	Indirect injection
110% Fuel Consumption (prime) L/H	5.9
100% Fuel Consumption (prime) L/H	4.9
75% Fuel Consumption (prime) L/H	TBA
50% Fuel Consumption (prime) L/H	TBA
Silence Type	Industrial
Lube Oil brand	15W40-CH4 Upgrade
Cooling System	Water cooled

Alternator Specification

Model	PI044G
Frequency and Speed	50Hz/1500rpm
Manufacturer	Stamford
Prime capacity(kVA)	15
Exciter type	Brushless
Insulation	Class H
Protection	IP23
Rated power factor	0.8
Stator winding	Double layer concentric
Winding pitch	two thirds
Winding leads	12
Maximum over speed	2250Rev/min
THF (Wave Form IEC)	<2%
TIF (Wave Form NEMA)	<50
Voltage regulation	1.00%