

Vacc-Safe Medical refrigerators are suitable for storing vaccines, medicines and laboratory products between 2°C and 8°C in pharmacies, hospitals, medical clinics and laboratories.



### Self Closing Door

Avoid letting the heat in by accident.



### Security

Audible and Visual Alarms. Safety Lock.



### Single LED Display

High accuracy single LED displays.



### DC Turbo Fan

Decreases noise level by 8% while increasing efficiency.



### Lockable

Additional security for pharmaceuticals and samples.



### Built-In Air Duct

Increases the effective interior space by 10%.



## High Precision Temperature Control.

Vacc-Safe® vaccine and medical cooling storage enables high precision temperature control and accuracy within 0.1°C giving the utmost confidence that goods are stored with precision. LBA Foaming Technology provides more effective insulation to improve performance and reduce overall energy consumption.



## Increased Product Lifespan

Powerful heat dissipation for condenser, heat exchange capacity increase by more than 20% than common copper tube fin condenser. Excellent compressor overheating protection, effectively improving the service life of core parts..

## Strong Cooling Airflow.

Strong cooling airflow from the top to the bottom, works as an air curtain to block the external hot air from entering the refrigerator when the door is opened.



## Improved Cooling Performance.

Our patented Smart-Inverter technology significantly reduces the amount of energy consumed whilst maintaining superior temperature stability. Enjoy improved cooling performance with variations less than 2°C, a 15% reduction in energy consumption and reduced noise level.

Item	Model No.	VS350
<b>Product structure data</b>	Temperature Range	2~ 8°C
	Fridge Storage Volume(L)	316 L Nett
	Product Dimensions(mm) (wxdxh)	595*603*1920
	Interior Dimensions(mm) (wxdxh)	500*464*1343
	Packing Dimensions(mm) (wxdxh)	660*665*2025
	Net/Gross Weight	78/90
<b>Technical data</b>	Compressor type	Fixed frequency
	Cooling Type	Forced air cooling
	Defrost type	No frost
	Climate Class	N
	Rated Voltage/Frequency(V/Hz)	220V/50Hz
	Rated Power(W)	190
	Rated Current(A)	1.5
	Decibel rating	52
<b>Control</b>	Refrigerant/Amount(g)	R600/36g
	Temp HI/LOW reset	N
	Sensor Qty	3
	Sensor Type	NTC
	Controller	Microprocessor
<b>Product Performance</b>	Display	LED display
	Temperature Accuracy	0.1 °C
	Temperature uniformity/°C	≤2°C
<b>Alarms</b>	Sound Alarm	Y
	Light Alarm	Y
	Power Failure Alarm	Y
	Sensor Failure Alarm	Y
	Environment Temperature Alarm	Y
	Door ajar Alarm	Y
	High Temperature Alarm	Y
	Low Temperature Alarm	Y
<b>Accessories</b>	Remote Alarm	N
	USB	N
	Anti-condensation Door	N
	Lock	Y
	Backup Battery	N
	Backup Battery Endurance	N/A
	Shelves/Drawers Qty	5 Shelves
	Cable Port	Y
Castors/type	4 (2 omni directional)	

