



Distributed by:

EXPLORER™ G2 3600 psi • 15 l/pm



Hot Water



Petrol Driven



Daily Usage

FIELDS OF APPLICATION

- Councils
- Poultry Sheds
- Painting Contractors
- Cleaning Contractors
- Boat Yards and Ports
- Agricultural Equipment
- Trains Depots and Sheds
- Car and Equipment Yards




NEW

The Jetwave® Explorer™ G2 heavy duty professional hot water petrol powered by HONDA™ pressure washer is revolutionary in its design and innovation. Australian engineered and assembled using only the best quality Italian and global components; it offers an industry first multi configurable modular kit to maximise space and efficiency.



Part No.: TROLLEYKIT



HERO INNOVATIONS

- Protection**
Formed steel cover to safeguard components and for work site safety.
- Smart**
Industry first customisable modular build with precision heavy gauge, steel chassis. Build it your way.
- Functional**
Easily accessible singular panel mounted control(s).
- Optimise**
Anti-vibration protection for a quieter reliable performance.
- Convenient**
Top lifting eyelets and forklift tyne pockets for onsite lifting ability.
- Featured**
J5000™ Durotech™ Gun with swivel and ceramic ball.
- Versatile**
Multiple hose reel configurations.

STANDOUT FEATURES

- Professional Italian triplex Interpump® pump delivers performance and longer life.
- Low speed professional pump for increased reliability and longer maintenance intervals.
- HONDA™ iGX390 Industrial Series Engine.
- Dual M22 screw hose coupling system.
- Vertical 90% fuel efficient environmentally friendly 12V diesel fired hot water burner system.
- Washable water inlet and diesel filter to ensure clean trouble free supply.
- GeniSys™ 12V Advanced Burner Control:
 - Delay cooling feature
 - Epoxy moisture resistance
 - Welded relay protection
 - High ambient temp rating
 - Interrupted ignition
 - Flame sensor / photo eye
- Quality pressure gauge.
- Easy electric key start with maintenance free battery in a protective box.
- Integrated accessory storage for gun and lance.
- Professional line accessories.
- Zero line pressure adjustable unloader valve.
- Emergency stop protection.



Jetwave Group
 72-74 Richmond Road
 Keswick | Adelaide
 South Australia | 5035 | AU
 +61 8 8371 3599
 sales@jetwave.com.au
 jetwave.com.au

Compacy - Modular frame design with top lift panels.

Protection - Designed for durability and a long life.

Control - Fascia mounted controls with plug n' go functionality.



Robust - Frame with gun and lance holder.

Power - Easy start HONDA™ GX390 engine.

Quality - Industry proven 'Italian' pump.

Flexibility - Multi configurable compact frame.

STANDARD EQUIPMENT



Spray Gun - J5000™ heavy duty insulated back part lance and quick coupling.

Lance / Nozzle - Stainless steel dual lance with variable pressure control complete with hardened nozzles.

Hose - 15m of 3/8" double wire braided hose with quick coupling.

OPTIONAL ACCESSORIES

1. Complete Turbo Head with Lance	p/n	JWA160.04
2. Additional High Pressure Hose (per metre)	p/n	52001
3. High Pressure Swivel	p/n	26105000
4. LS3-1 Foaming Lance with Tank	p/n	JWA221-LS12
5. High Pressure Hose Reel (cap 30m / 60m)	p/n	1060CMPL 1065CMPL
6. Hammerhead™ Whirlaway 20" ABS	p/n	JWA-FSC21.04
7. Hammerhead™ Whirlaway 22" Stainless Steel	p/n	JWA-FSC2255.04
8. Giraffe™ Telescopic Lance	p/n	DCLTG24A4
9. Sandblasting Kit	p/n	JWA164
10. Sludge Kit	p/n	80005
11. Drain Kit	p/n	HOP3X15-BLACK
12. 316 Grade 2.5mm Stainless Steel Heating Coil	p/n	JWA322

MACHINE OPTIONS

1. 4 Wheel Trolley Kit	p/n	ER4WKI
2. 2 Wheels / 2 Castor Wheels with Brake Kit	p/n	ER2W2CWKI
3. Flat Bed Mounting Kit	p/n	ERFBMKITI
4. Side Mount Kit	p/n	ERBMSKI

Product Code	p/n	HW3600-15PG2
--------------	-----	--------------

TECHNICAL DATA

Working Pressure	psi / bar	3600 / 250
Flow Rate	l/pm	15
Max Water Inlet / Outlet Temp	°c	60 / 90
Class (AS/NZS: 4233)	grade	A

INTENDED APPLICATION

Usage Frequency	hours / type	4 - 6 daily / Constant
Category of Dirt / Debris	type	Medium

MOTOR FEATURES

Engine	type	HONDA™ iGX390 (4 stroke, air cooled)
Power	hp / cc	13 / 390
Fuel Supply	type	Unleaded
Fuel Capacity	litres	6.1
Low Oil Shutdown	y / n	Y (indicator light)
Hour Meter	y / n	N
Starting System	type	Electric key start

HYDRAULIC FEATURES

Pump	type	Interpump® Plunger Triplex / Brass / Ceramic
Motor Pump Coupling	type	Gearbox Drive
Pump Speed	rpm	1450
Unloader Valve	type	Independant (Zero)
Safety Valve	y / n	Y
Orifice / Nozzle	size	040

OTHER FEATURES

Electric / Key Start Available	y / n	Y
Adjustable Pressure	y / n	Y
Hose Reel Provision	y / n	Y / 3 Positions
Frame Structure	type	Modular skid with heavy gauge steel and powder coated covers
Onboard Accessory Storage	y / n	Y
Detergent Injector	y / n	Y - Downstream low pressure adjustable

THERMAL FEATURES

Burner Model	type	Vertical 12V V1
Fuel Supply	type	Diesel
Fuel Tank Capacity	litres	27
Burner Fuel Consumption (max)	l/ph	5.74
Coil	type	Mild steel 3mm wall seamless
Housing Material	type	Stainless Steel

DIMENSIONS & WEIGHT

Approx Weight	kg	270 unit / 285 boxed
Unit Dimensions	mm	1300(L) x 950(W) x 1070(H)
Boxed Dimensions	mm	1320(L) x 740(W) x 960(H)
Number per Pallet	type: pieces	AS: 2 / Euro: 1

WARRANTY(S)

Motor Warranty	years	3	
Warranty	years	1	

*Coverage against defects in material and workmanship (refer to Jetwave's and component partners T&Cs).

POWERED by
HONDA

The manufacturer reserves the right to modify design features and technical facts without notice, due to our principals of continuous improvement.
 V1.0 11/2018