

JIALIFT®



www.jialift.com.au

SPN1025 Semi - electric Stacker

- 1000kg Capacity; Max Lifting Height - 2500mm
- Walk-behind operate no license required
- Safe, reliable, sustainable and low maintenance

CE

JIALIFT Semi-electric Walkie Stacker (1T/2500mm)

With electric lift and manual push, SPN series semi-electric pallet stacker is easy to control, and environmental efficiency, which is widely used in overhead cargo and pallet moving and stacking.

Using SPN is safe and efficient in factories, warehouses, and logistics centres. While in some narrow passage, floors, and other high rack warehouses, using SPN is more flexible, silent and environmental.

This model is used for open pallet, NOT for Australia standard pallet (CHEP). It offers a number of **advantages**:

- Walk-behind operate no license required.
- Control Panel: Fascia-mounted control panel with raise/lower buttons, emergency stop trigger, battery indicator and hour-meter.
- The in-built charger is single phrase (wall plug) can be easily charged
- Adjustable Fork: Forged forks with an adjustable width. Easy service and maintenance
- Lockable wheel: Wheels: Brake-enabled with 360-degree rotation. Large diameter steered rear wheel for easy movement across any surface.

Warranty: 5 Years refer to the JIALIFT warranty terms and conditions



JIALIFT AUSTRALIA PTY LTD

Call Us: 1300 000 168 Email: sales@jialift.com.au


46-48 Geddes St, Mulgrave VIC 3170 Open at 8:30 am - 5:30 pm, Monday-Friday



www.jialift.com.au

JIALIFT®

MATERIAL HANDLING EQUIPMENT



JIALIFT AUSTRALIA PTY LTD

Call Us: 1300 000 168 Email: sales@jialift.com.au

46-48 Geddes St, Mulgrave VIC 3170 Open at 8:30 am - 5:30 pm, Monday-Friday



www.jialift.com.au

JIALIFT®

MATERIAL HANDLING EQUIPMENT

Distinguishing mark		
Model designation		SPN1025
Load capacity	kg	1000
Load capacity on max. Height	kg	700
Max lifting height	mm	2500
Load center distance	mm	600
Weight		
Service weight	kg	374
Dimensions		
Fork length	mm	1150
Single fork width	mm	150
Overall fork width	mm	Narrow550/Standard640
Lowered fork height	mm	85
Fixed leg length	mm	875
Single fixed leg width	mm	100
Inner width of two fixed legs	mm	390
Outer width of two fixed legs	mm	590
Turning radius	mm	1350
Overall length	mm	1600(900Fork)/1800(1100Fork)
Overall width	mm	760
Extended mast height	mm	3067
Lowered mast height	mm	1827
Types, Chassis		
Wheels type		NL
Front wheel size, number	mm	74x70, 2
Rear wheel size, number	mm	180x50, 2
Electric-engine		
Lift motor rating	kW	1.5
Lift motor	V	12V
The charger		12V/20A
Battery voltage/nominal capacity		12V/120AH



JIALIFT AUSTRALIA PTY LTD

Call Us: 1300 000 168 Email: sales@jialift.com.au

46-48 Geddes St, Mulgrave VIC 3170 Open at 8:30 am - 5:30 pm, Monday-Friday

www.jialift.com.au