



TECHNICAL DATA

EXTERNAL DIMENSIONS

width	990 mm
depth	885 mm
height	2140 mm

WEIGHT(basic version)

240 kg

VOLTAGE

400V 3N 50Hz

POWER REQUIRED

13360 W

WATER HARDNESS

 $< 8 \text{ }^\circ\text{F}$

WATER CONDUCTIVITY

 $> 200 \text{ } \mu\text{S/cm}$

INLET WATER PRESSURE

200-400 kPa

CROCKERY DIMENSIONS

size allowed 655 mm

RACK DIMENSIONS

850X725 mm

RACK EQUIPMENT

1XC86/A - 1XC97/A - 1X92100

WASHING CYCLES

(min)

1 (4)

2 (7)

3 (10)

4 (13)

WATER SUPPLY 10°C

racks/h(*)⁽¹⁾

15

8

6

4

WATER CONSUMPTION / CYCLE

4,3 L

BOILER CAPACITY

15 L

BOILER HEATING ELEMENT

9000 W

RINSING TEMPERATURE (SET)

85°C

TANK CAPACITY

82 L

TANK HEATING ELEMENT

6000 W

TANK TEMPERATURE (SET)

55°C

WASHING PUMP POWER

 2180 W (810 l/min^{***}) × 2

RINSING PUMP POWER

 250 W (150 l/min^{***})

DRAIN PUMP (optional)

 190 W (120 l/min^{***})

ACOUSTIC PRESSURE

71,1 dB(A)

(*) STANDARD THERMOSTOP

(***) MAXIMUM FLOW RATE

⁽¹⁾ In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.