



**PRODUCTS**

- [Fiber Rotary Joints](#)
- [Electrical Slip Rings](#)
- [Fiber Components](#)
- [Fiber Polishers](#)

**SERVICES**

- [Fiber Termination](#)
- [Outdoor Fiber Patchcords](#)
- [Laser Pigtailling](#)
- [Training](#)

**SOLUTIONS**

- [Sliprings](#)
- [RF Rotary Joints](#)
- [Fluid Rotary Unions](#)
- [Multiplexers](#)
- [Media Converters](#)



Select Language

Powered by [Google Translate](#)

ShareThis



609.895.9890



609.895.9552

**Accessories: Polishing Disks**



PD318 (SMA905)  
[CLICK for larger view](#)

Princetel's polishing fixtures consist of polishing disk/disks and a polishing disk holder. The two smaller polishers, FP180 and FP180e, require one polishing disk while the large one, FPM30, requires a total 6 polishing disks. It is possible to mix different polishing disks on the larger polisher. For best results, however, we recommend mounting disks that fit the same diameter ferrules.

The following table lists all standard polishing disks. Custom disks with special diameter or angle are possible with a moderate NRE charge.

**FEATURES**

- Inter-changeable design makes them fit all Princetel's polishing machines
- Hold up to two connectors or ferrules simultaneously on a single disk
- Simple mounting procedure to change disks
- Low cost solution for all standard and custom polishing needs
- Quick turn-around for custom polishing disks
- Locking two connectors/ferrules with one twist action
- Ideal for termini/pin polishing

**STANDARD DISKS**

MODEL NUMBER	DESCRIPTION
PD125	1.25 mm (LC or ferrules with 1.25 mm diameter)
PD125A	1.25 mm (LC/APC or ferrules with 1.25 mm dia.)
PD160	1.60 mm (ferrules with 1.60 mm diameter)
PD160A	1.60 mm (8 deg; ferrules with 1.60 mm diameter)
PD180	1.80 mm (ferrules with 1.80 mm diameter)
PD180A	1.80 mm (8 deg; ferrules with 1.80 mm diameter)
PD200	2.00 mm (ferrules with 2.00 mm diameter)
PD200A	2.00 mm (8 deg; ferrules with 2.00 mm diameter)
PD250	2.50 mm (FC, SC, ST and ferrules with 2 mm dia)
PD250A	2.50 mm (FC/APC, SC/APC and ferrules)
PD318	3.18 mm (SMA 905 and ferrules)
PD318A	3.18 mm (8 deg; SMA 905 and ferrules)