

# ITA 62

STEEL STRAPPING TOOL > PNEUMATIC

## Low Pressure Pneumatic Steel Strapping Tool with Seal for 19mm / 25mm / 32mm Steel Strap

ITA 62 a the combined double notch seal joint pneumatic steel strapping tool for 19mm / 25mm / 32mm steel straps.

Specially studied to work also with Low pressure (from 4.5 Bar), ITA 62 is the most suitable tool in case of long air connections.

This tool is equipped with 2 operating buttons, to allow Automatic tensioning of Your steel strap.

ITA 62 is available in two motor versions (9000 N and 15000 N) to provide the most suitable and adjustable tension for Your application.

Easy to be used, ITA 62 is already equipped with its suspension hook to grant a lighter operation mode to arrange a perfect double notch seal joint.

Powerful, quick and strong, ITA 62 is manufactured to be durable and with very low maintenance required.



### FEATURES

Working at Low Air Pressure (from 4.5 Bar)  
2 Operating Buttons  
Strong and Reliable  
Easy to be used  
Low Maintenance Required  
Powerful and Quick

### BENEFITS

Double Notch Seal Joint  
Automatic Tension  
Robust and durable  
For a wide range of steel Straps  
Suspension hook already equipped

#### TECHNICAL SPECIFICATION

<b>Dimensions</b>	430 x 260 x 310 mm
<b>Weight</b>	11,3 Kg

#### STRAP

<b>Type</b>	Steel Strap - regular & high tensile
<b>Width</b>	19mm / 25mm / 32mm
<b>Thickness</b>	0,6mm - 1,0mm (Regular duty) 0,63mm - 0,8mm (High Tensile)

#### POWER SUPPLY

<b>Pressure Range</b>	4.5 - 7 bar (78 - 99 psi)
<b>Air Consumption</b>	12 L/s - 25 cuft/min

#### PERFORMANCE

<b>Max. tension force</b>	7000N (4,5 bar - 65psi) 15000N (6 bar - 87 psi)
<b>Tensioning Speed</b>	4,0 mt/min @15000N
<b>Sealing</b>	Seal Double Notch
<b>Joint Strenght</b>	75% of breaking strenght*

\* variable according to strap type

#### MODEL

CODE	DESCRIPTION
T621943	ITA 62 - 19mm Steel - 9000N
T622543	ITA 62 - 25mm Steel - 15000N
T623243	ITA 62 - 32mm Steel - 15000N