

The all new SWIR camera by **pco.**



VIS & SWIR sensitivity
400 to 1700 nm

small pixel size
5 μm x 5 μm

long exposure times
due to low dark current

excellent peak QE
of 90 %

interface	USB 3.1 Gen 1
sensor technology	InGaAs
spectral range [nm]	400 to 1700
resolution [pixel]	1280 x 1024
sensor diagonal [mm]	8.2
pixel size [μm]	5 x 5
max. frame rate @ full resolution [fps]	71.5 (12 bit)
max. pixel rate [MPixel/s]	93.7 (12 bit)
peak QE	90 % @ 1200 nm
typ. read noise ¹ [e ⁻]	< 200
dark current @ sensor temperature [e ⁻ /pixel/s]	2000 @ +5 °C
max. dynamic range	680:1
shutter type	GS (Global Shutter)
sensor cooling ²	air
dimensions H x W x L [mm]	70 x 70 x 115

¹ The readout noise values are given as root mean square (rms).

All values are raw data without any filtering.

² air = air forced with fan

Extend the vision to SWIR

The SWIR camera from PCO is a high performance machine vision camera, which is due to its special InGaAs image sensor sensitive in the shortwave infrared, near infrared and visible range of the electromagnetic spectrum. It shows a favorably high sensitivity in the whole spectral range with more than 85 % in the shortwave infrared part. Due to its small pixels the camera enables the use of small magnification optics in microscopy and a low dark current to enable even longer exposure times.

Distributed by



MEL: (03) 9480 4999
SYD: (02) 9705 8059
sales@scitech.com.au
www.scitech.com.au

preliminary

pco.

An Excelitas Technologies Brand

subject to changes without prior notice
© Excelitas PCO GmbH, Kelheim | pco. SWIR camera flyer | v1.00