

UNITED

Forklift and
Access Solutions



HTA13 / 16 / 19 P

Trailer Mounted Boom

Haulotte >>

Access on the move

- > Hydraulic outriggers and automatic leveling allow operation in under 30 seconds.
- > Superior combination of industry leading capacity and outreach.
- > Can be towed by a standard half-ton pickup truck - No commercial driver's license needed

Exceptional productivity

- > Air / water lines and 110V GFI protected power to the platform.



UNITED It's all about you

TECHNICAL DATA		HTA13 P	HTA16 P	HTA19 P
Working height		12.73 m	15.40 m	18.67 m
Platform height		10.90 m	13.72 m	18.84 m
Horizontal outreach (from centerline)		8.86 m	8.23 m	10.19 m
Horizontal outreach (from edge of footpad)		5.31 m	6.40 m	8.33 m
Up and over height		5.79 m	6.33 m	7.04 m
Lift capacity		227 kg		
A	Length - stowed	4.96 m	5.94 m	6.99 m
B	Width stowed	1.67 m	1.67 m	1.70 m
C	Height stowed	1.96 m	1.96 m	1.98 m
D x E	Platform size	1.22 x 0.76 m		
F	Widest Point	3.60 m	4.19 m	4.47 m
G	Widest Point	3.40 m	4.11 m	4.57 m
Turntable rotation		350° non-continuous		
Jib - length		1.30 m		
Jib - Vertical motion		150° (+70 / -80)		
Tow speed rating				
Leveling capability		12.5°		
Tire size		ST 225/75 D15	ST 225/75 R15	ST 225/75 R15
Power source		4 x 6 V 245 Ah		
Tongue weight (no options)		111 kg	132 kg	152 kg
Weight (no options)		1,542 kg	1,905 kg	2,177 kg

STANDARD EQUIPMENT

- Hydraulic Outriggers
- Tilt alarm / sensor
- Hour meter and battery condition indicator
- Automatic levelling system and self-levelling platform available
- 110V GFI protected outlet to platform
- Easy to use controls
- Air and water line to platform
- Inboard 25 amp charger
- Integrated forklift pockets
- Hydraulic surge brakes (trailer)

OPTIONS

- Reflective tape
- 240 Volt power outlet
- 1.0 kg fire extinguisher
- Lockable battery isolator switch

