



<14.4 km
Range per Charge



120 kg
Weight Capacity



125 cm
Turning Radius



GO GO[®]e

The simple solution to urban travel

Get wherever you need to go on the GoGo[®]-e mobility scooter. Streamlined steering controls guarantee user-friendly operation. Equipped with a front basket for added convenience and a comfortable seat, the GoGo[®]-e is the perfect cost-effective choice for individuals seeking a straightforward solution for urban travel on paved paths and sidewalks.





8" Front and Rear Solid Wheels



Front Basket



Easy to Use and Steer Controls

RANGE PER CHARGE (MAX) ^{1,3}	14.4 km at 120 kg
MAXIMUM WEIGHT CAPACITY	120 kg
TURNING RADIUS ²	125 cm
MAXIMUM SPEED ¹	6.4 km/h
LENGTH & WIDTH ^{2,5}	L: 100 cm W: 49 cm
SEAT TYPE DEPTH & WIDTH (STANDARD)	Molded plastic, black vinyl D: 33 cm (13") W: 41.9 cm (16.5")
SEAT-TO-DECK HEIGHT ²	41.9 cm - 45.7 cm
SEAT-TO-GROUND HEIGHT ²	54.6 cm - 59.7 cm
GROUND CLEARANCE ^{2,4}	5 cm at transaxle

OVERALL WEIGHT (NOT INC BATTERY) ^{2,6}	32.5 kg
WEIGHT OF HEAVIEST PIECE ²	31 kg (main frame - does not disassemble)
SUSPENSION	N/A
3W/4W OPTION	4W
FRONT TYRES ²	8" solid
REAR TYRES ²	8" solid
BATTERY REQUIREMENTS ⁸	(2) 12AH
BATTERY CHARGER	Off-Board, 2A
BATTERY WEIGHT ²	2.5 kg each
COLOUR OPTIONS	■ Matte Black

1. Varies with user weight, terrain type, battery amp hour (AH), battery charge, battery condition and tyre condition. This specification can be subject to a variance of 10%.
2. Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of 3%.
3. Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 and ISO 7176-4 standards. Results derived from the theoretical calculations based on battery specification and drive system performance. Test conducted at maximum weight capacity.
4. Does not account for anti-tip clearance.
5. Width of base (not including seat).
6. Includes standard seat weight.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of 3%. Special order seats or non-standard dimensions will not fold-flat and depth-adjustable.