



Ex PORTLAND

PATHWAY / STREET LIGHT

- + Lightweight, slimline street/path lighting for hazardous areas
- + Highly efficient at >120 -200lm/W
- + Suitable for corrosive, water or dust prone environments IP66/WF2
- + Excellent heat dissipation performance

Certifications & Compliance

- + Ex d e mb IIC T6
ATEX, IECEx, CE, RoHS, IP66



Application

- Power Stations
- Marine Industries
- Petrol Stations
- Petrochemical Industries
- Railway Stations
- Large Workshops
- Disaster Relief
- Industrial Areas

Electrical Parameters

MODEL	ETG-EXPORT100	ETG-EXPORT120	ETG-EXPORT160	ETG-EXPORT200
Rated power	100W	120W	160W	200W
Input Voltage	AC 100~270V 50/60Hz			
Luminous Flux (lm)	12,000	14,400	19,200	24,000
Driver	Meanwell			
Led Source	Cree 3030			
PF	>0.95			
CRI	Ra>70 - 75			
Luminous Efficacy	120 lm/W			
IP / Anti-Corrosion Rating	IP66 / WF2			
Operating Temp	-30°C ~ +50°C			
CCT	3000~6500K			
Beam Angle	100°			
Ex-Proof Grade	Ex d e dII C T6			
Lifespan	100,000 Hours			
Dimensions (mm) & Weight (kg)	567 x 276 x 74 (LWH) 10.5			
Warranty	5 Years			