TOUCH SCREEN ELECTRONIC SCALE













TOUCH SCREEN TFT

UP TO 10,000 PLUs

20 VENDORS









Characteristics and functionality

Main characteristics

- Touch screen scale with conventional electronics (no PC).
- Models with receipt printer, label printer (suitable for receipts) or with 2 printers (for receipts and labels).
- Variety of formats.
- Modern, compact and easy to clean design.
- More intuitive user menus.
- More dynamic and stylish buyer screen as an advertising tool.
- Configurable and customized flat vendor screen.
- Compliance with EU Regulation 1169/2011 on the provision of food information to consumers.

Features

- Extensive information for each PLU: normal price and offer price, price for weight ranges and by kg/100 g, 3 names of 20 characters or 2 names of 30 characters, 20 free texts of 24 characters, 1 text of 3,000 characters (in D-955 and D-957), etc.
- PLUs search by codes or name.
- Access to all functions of the user and technical menus from the vendor screen (possibility of programming security passwords).

- Customization of the screens:
- > Selection of the most frequent functions in "Favourites".
- > Screen design with corporate colours and logos.
- > Allocation of independent direct keys by section and alphabetic order of the PLUs.
- > Preset keys for PLUs, sections and vendors, whereby the image, quantity and size can be configured.
- Direct uploading of images from pen drive (8 bits bmp format without RLE compression).
- Sales and management reports: sales (by article, vendor, time frames, last month, etc.), margins, balance available in the cash drawer, modified PLUs, etc.
- Export of lists to USB (total sales per employee, per payment method, per VAT rate).
- Export of receipts to USB.
- Cross selling: showing the picture of a complementary product on buyer display when selling a product.
- Fast and reliable communication between scales, with PC and mobile devices (via DWS).
- Stock management by article on the scale.
- Option to record normal price and offer price for each article.
- Warning of low level of labels in the scale, and activating light and acoustic signs.

Capacity / Accuracy

- Multi-range (3,000 divisions): 6 kg / 2 g 15 kg / 5 g.
- Optional:
 - > Mono-range (3,000 divisions): 15 kg / 5 g or 30 kg / 10 g.
 - > Multi-range (3,000 divisions): 15 kg / 5 g 30 kg / 10 g.
 - > Mono-range (6,000 divisions): 12 kg / 2 g or 30 kg / 5 g.

Available formats

- Flat.
- Pole.
- Double body.
- Hanging.
- Self-service.

Construction

- Highly resistant ABS plastic casing in counter format.
- Stainless steel casing in hanging formats.
- Stainless steel plate.
- Access to all non-metrological components without the need to unseal the scale.

Displays

- Vendor: Configurable 12.1" touch screen TFT in double body, hanging and self-service formats (W250 x H188 mm); 10.4" in flat, pole and flat self-service formats (W215 x H161 mm) and 15" in double body self-service format.
- Buyer: 7" TFT (W191 x H122 mm) with adjustable inclination, or 12.1" TFT (with adjustable inclination and height). Allows showing advertising or promotional images even during the selling operation; or the turn (managed from the scale).

Printer(s)

- Models available with 1 printer for receipts, 1 printer for labels (also suitable for receipts by changing the paper roll and the working mode) or with 2 printers (for receipts and labels).
- 54 mm thermal printer.
- Resolution: 8 dots/mm; speed: 100 mm/sec.
- Cassette for immediate paper roll change (in label printers).
- Optional:
- > Linerless (in label printers).

Receipts

- 15 fonts (6 monospaced + 9 multispaced: more modern and legible).
- Up to 75 items.
- 2 fixed formats + 2 programmable formats.
- 4 logos.
- Barcodes: EAN-13, GS1 DataBar, EAN-128, Code 128 and OR *
- > Possibility of printing QR codes, for example, for ticket breakdown.
- Name of vendor.



- 9 payment methods.
- Total in National currency and other 3 currencies.
- Discounts per line and total.
- Loyalty points.
- Customers on account.
- Recipes.

Labels

- 15 fonts (6 monospaced + 9 multispaced: more modern and legible).
- From W30 x L30 mm to W60 x L150 mm.
- 20 fixed formats + 40 programmable formats.
- 100 logos.
- Barcodes: EAN-13, GS1 DataBar, EAN-128, Code 128 and QR.*
 - > Possibility of printing QR codes, for example, for ticket breakdown.
- 60 fields of information.
- 100 programmable texts.
- Manual and automatic pre-packing modes.
- 3 levels of totals.
- Printing of "n" identical labels.
- Printing with 90°, 180° and 270° rotation.
- Automatic adjustment of the paper detection s
- Packaging date, expiry date and extra date (for any application).
- Alphanumeric batch number.
- 10 types of generic traceability (for meat, fish, fruits, vegetables, etc.) up to 99 products. Included in the prevailing European legislation on bovine traceability.



^{*} It prints the following barcodes: EAN-13, GS1 DataBar, EAN-128, Code 128 and QR; it reads the following barcodes: EAN-13, EAN-128 and QR.



Food information

- Compliance with EU Regulation 1169/2011 on the provision of food information to consumers as of 13 December 2016:
- > Minimum letter size: 1.2 mm.
- > Effect (**bold**, <u>underlined</u>, or <u>both</u>) for each character in the text.
- > Possibility of using the general text "G" (3,000 characters) for ingredients, in lower case or UPPER CASE to highlight allergens.
- > Possibility of including a table of nutritional facts.
- > Free texts (20 x 24 characters).
- > For direct sale receipts and labels: possibility of indicating in the PLU name (with an * or other symbol) those that contain allergens and programming a text, such as "* Consult allergens".
- > Possibility of printing 2 labels for each operation: programmable by PLU, configurable information, 2nd automatic or manual label (also to be used as promotional labels).

Communications

- TCP/IP Ethernet for interconnection and connection to PC.
- RS-232. for connection to scanner.
- USB.
- Optional:> Wi-Fi.

Security

 Access to different protected programming menus via configurable passwords.

Interconnection

• Up to 16 scales per section.

Connectivity with other devices

- PC.
- Barcode scanner (powered by the scale –5 VDC–) to read EAN-13, EAN-128 and QR barcodes. Optional built-in scanner, for double body format.
- Cash drawer.
- Queueing system (for hanging scales).
- Connectable to a single load cell weighing platform, up to 400 x 400 mm max., and up to 30 kg. Consult compatible scales formats.

Software

(See section on software)

PC software:

- DFS:
 - > Programming of scales.
- > Receipt of sales data.
- > Data backup copy.
- > Graphic design of receipts and labels (DLD).
- > Design and management of advertising images for buyer display.
- Integration tools: in Windows or Linux to facilitate communication with the Back-Office.

Scale firmware:

- DWS (Dibal Web Server):
- > Allows access to the information on each scale (via passwords) from any computer or mobile device with an Internet browser.

Power supply

- Mains: 110 up to 230 VAC.
- Optional:
- > Anti-blackout rechargeable internal battery 24 V and connector to external battery 24 V.

Energy consumption

• 16.5-90 W (depending on the conditions of use).

1 RECEIPT PRINTER



	Vendor Display	Buyer Display	Printer	PLUs	Direct PLUs	Vendors	Power	Capacity / Accuracy	Reference
D-950 DB 12 + 7	12.1" touch screen TFT	TFT 7"	Receipts	10,000	999	20	Mains	6 kg / 2 g -15 kg / 5 g	7D705D5LGE
D-950 DB 12 + 12	12.1" touch screen TFT	TFT 12.1"	Receipts	10,000	999	20	Mains	6 kg / 2 g -15 kg / 5 g	7D706D5LGE






1 RECEIPT PRINTER

S. Steel Hanging Format



Dimensions



Α	436
В	126
C	300
D	415
Plate	e dimensions: Ø 310 mm

Weight with packaging: 11.0 kg.



	Vendor Display	Buyer Display	Printer	PLUs	Direct PLUs	Vendors	Power	Capacity / Accuracy	Reference
D-950 H 12 + 7	12.1" touch screen TFT	7" TFT	Receipts	10,000	999	20	Mains	6 kg / 2 g -15 kg / 5 g	7D705C5SIE
D-950 H 12 + 12	12.1" touch screen TFT	12.1" TFT	Receipts	10,000	999	20	Mains	6 kg / 2 g -15 kg / 5 g	7D706C5SIE



Flat Format




Dimensions

DATA IN mm

A 382
B 520
C 180

Plate dimensions: L360 x W260 mm. Weight with packaging: 12.5 kg.











	vendor Display	Buyer Display	Printer	PLUs	PLUs	Vendors	Power	Capacity / Accuracy	Reference	
D-955 P 10 + 7	10.4" touch screen TFT	7" TFT	Labels (or Receipts)	10,000	999	20	Mains	6 kg / 2 g -15 kg / 5 g	7D755T5LGE	





	Vendor Display	Buyer Display	Printer	PLUs	Direct PLUs	Vendors	Power	Capacity / Accuracy	Reference
D-955 DB 12 + 7	12.1" touch screen TFT	7" TFT	Labels (or Receipts)	10,000	999	20	Mains	6 kg / 2 g -15 kg / 5 g	7D755D5LGE
D-955 DB 12 + 12	12.1" touch screen TFT	12.1" TFT	Labels (or Receipts)	10,000	999	20	Mains	6 kg / 2 g -15 kg / 5 g	7D756D5LGE






S. Steel Hanging Format



Dimensions



DATA IN mm

Α	436
В	126
С	300
D	415
Dlete	dimensions Ø 210 mm

Weight with packaging: 13.0 kg.





Cassette included.

	Vendor Display	Buyer Display	Printer	PLUs	Direct PLUs	Vendors	Power	Capacity / Accuracy	Reference
D-955 H 12 + 7	12.1" touch screen TFT	7" TFT	Labels (or Receipts)	10,000	999	20	Mains	6 kg / 2 g -15 kg / 5 g	7D755C5SIE
D-955 H 12 + 12	12.1" touch screen TFT	12.1" TFT	Labels (or Receipts)	10,000	999	20	Mains	6 kg / 2 g -15 kg / 5 g	7D756C5SIE



1 LABEL PRINTER

Flat Self-Service Format




Dimensions

DATA IN mm

Α	382	
В	481	
C	180	

Plate dimensions: L360 x W260 mm. Weight with packaging: 12.0 kg.





	Front Display	Back Display	Printer	PLUs	Direct PLUs	Vendors	Power	Capacity / Accuracy	Reference
D-955 F SS 10	10.4" touch screen TFT	-	Labels	10.000	999	-	Mains	6 kg / 2 g -15 kg / 5 g	7D750P5LGE

(M) optional



1 LABEL PRINTER



	Front Display	Back Display	Printer	PLUs	Direct PLUs	Vendors	Power	Capacity / Accuracy	Reference	
D-955 DB SS 12	12.1" touch screen TFT	-	Labels	10,000	999	-	Mains	6 kg / 2 g -15 kg / 5 g	7D750D5LGE	



1 LABEL PRINTER



	Front Display	Back Display	Printer	PLUs	Direct PLUs	Vendors	Power	Capacity / Accuracy	Reference
D-955 DB SS 15	15" touch screen TFT	-	Labels	10,000	999	-	Mains	6 kg / 2 g -15 kg / 5 g	7D650D5LGE





2 PRINTERS (RECEIPTS AND LABELS)



	Vendor Display	Buyer Display	Printers	PLUs	Direct PLUs	Vendors	Power	Capacity / Accuracy	Reference
D-957 DB 12 + 7	12.1" touch screen TFT	7" TFT	1 Receipt printer + 1 Label printer	10,000	999	20	Mains	6 kg / 2 g -15 kg / 5 g	7D775D5LGE
D-957 DB 12 + 12	12.1" touch screen TFT	12.1" TFT	1 Receipt printer + 1 Label printer	10,000	999	20	Mains	6 kg / 2 g -15 kg / 5 g	7D776D5LGE


(M) optional

2 PRINTERS (RECEIPTS AND LABELS)





Dimensions



Α	443
В	186
С	300
D	415

Plate dimensions: Ø 310 mm. Weight with packaging: 13.5 kg.





Cassette included.

	Vendor Display	Buyer Display	Printers	PLUs	Direct PLUs	Vendors	Power	Capacity / Accuracy	Reference
D-957 H 12 + 7	12.1" touch screen TFT	7" TFT	1 Receipt printer + 1 Label printer	10,000	999	20	Mains	6 kg/2 g-15 kg/5 g	7D775C5SIE
D-957 H 12 + 12	12.1" touch screen TFT	12.1" TFT	1 Receipt printer + 1 Label printer	10,000	999	20	Mains	6 kg / 2 g -15 kg / 5 g	7D776C5SIE

(M) optional



Options



> Built-in scanner in scale

Option	Characteristics	Ref.
Capacity 15 kg / 5 g	Mono-range (3,000 divisions).	N(*)
Capacity 30 kg / 10 g	Mono-range (3,000 divisions).	Y{*}
Capacity 15 kg / 5 g - 30 kg / 10 g	Multi-range (3,000 divisions).	F(*)
Capacity 12 kg / 2 g	Mono-range (6,000 divisions).	V{*}
Capacity 30 kg / 5 g	Mono-range (6,000 divisions).	P(*)
Linerless	Label or receipt on continuous adhesive paper without supporting paper (in label printers: D-955 and D-957).	Consult
Wi-Fi	Wireless communications (IEEE 802.11n).	Consult
Anti-blackout	Anti-blackout internal battery 24 V + external battery connector 24 V.	Consult
Built-in scanner in the scale	1D and 2D barcodes. Only for double body format.	Consult
		7340F1U1
DFS Software	Scale configuration, receipt of sales data for processing with other IT applications, data backup (LBS), and labels and receipts	7340FNU1
DFS SOftware	graphic design (DLD). (See section on software).	7340D1U1
		7340DNU1
Technical DWS Firmware	For the remote configuration of the scale.	7340W101
Full DWS Firmware	For the remote configuration of the scale and processing of the information generated. (See section on software).	7340WN01
Metrological verification (M)	According to EU weighing directives (See section on equipment metrological verification).	Consult

^(*) The scale references with this capacity are obtained by replacing the last characters of the reference for the standard scale with the indicated ending.

Accesories



Small Italian plate L357 x W235 x H55 mm.



Large Italian plate L407 x W284 x H60 mm.



Flat plate for hanging scales L360 x W280 mm, instead of the semi deep plate.



Ø310 x H70 mm, instead of the semi deep plate.



Barcode scanner

Includes connection cable to the scale. (For built-in scanner, consult options).



Adapter for receipt printing in label printer Required for standard size receipt rolls.

Note:

- The references correspond to standard models: Dark gray ABS plastic in counter format or stainless steel casing in hanging format, 15", 12.1" or 10.4" TFT touch screen in vendor side and 12.1" or 7" TFT display in buyer side (depending on format), stainless steel flat plate in counter scales (semi deep stainless steel plate in hanging scales), cash drawer connector (queueing system connector in hanging scales) and TCP/IP Ethernet communications. Capacity/Accuracy: 6 kg / 2 g – 15 kg / 5 g.