

#### Overview

Hot display units incorporating a wet well bain-marie and hot cupboard fitted with Moffat's renowned innovative sahara fan heating cell. Versigen were the originators of a bain-marie that could be either wet or dry heat. This type of system was designed to offer flexibility and was developed to eliminate the need to fit a low water level warning system or the expense of replacing burned out elements. Wet heat water level is an economic 20 mm deep, complete with drain valve and swing out run off tube for easy emptying/cleaning available in 4 lengths designed to accommodate 1/1 GN pans, These units incorporate a very efficient heating system, additional to the fully enclosed heating elements fitted under the bain-marie well, excess residual hot air from the hot cupboard is also used to maintain temperature. Designed to maintain pre-heated, cooked food at a regulated temperature. Suitable for the display of most types of hot foods, designed to accommodate various combinations of Interchangeable gastronom type pans up to 150 mm deep.



## **Key Features:**

- Fast heat up and recovery time
- Thermostatically controlled.
- Unique, removable, forced air heating cell.
- Low maintenance, easily cleaned, and highly efficient
- Gastronorm pans can be swapped out and replenished during service.
- A unique raised lip around the well allows the easy removal of pans.
- 4 models in the range holding 2 to 5 GN 1/1 gastronorm type containers.
- Various mixed sizes of gastronorm pans can be used in unison.
- 24 hour operation [bain-marie opening must be fitted with Pans or covers during service]
- Plug and Go, complete with 2 metre long power cable and plug
- Fully insulated
- Mobile all swivel castors two with brakes

# Options:

- Various heated / illuminated overhead gantry options
- Wide choice of coloured outer panels (durable plastic coated steel)
- Glass hot top adaptor [Neo-Ceram] (Code: DNCA)
- Round pot adaptor & 2 x 4.5 litre pots with lids(code: DRP4)
- Round pot adaptor & 2 x 7.0 litre pots with lids (code: DRP7)
- Gastronorm pans.
- Fold down solid tray slide or tubular tray rail



#### Note:

Low height models are available set at 800mm high. Ideal for children up to 12 years.


These low height models have a "B" added to the model code.

# Optional solid tray slide

| Model | Matching unit size |
|-------|--------------------|
| VC2TS | 2                  |
| VC3TS | 3                  |
| VC4TS | 4                  |
| VC5TS | 5                  |

### Optional tubular tray rail

| Model | Matching unit size |
|-------|--------------------|
| VC2TR | 2                  |
| VC3TR | 3                  |
| VC4TR | 4                  |
| VC5TR | 5                  |

















| VC2BMW   2   51   830 x 680 x 900   2 x 0.75   0.9   2.40   2.62   15amp |                       | Power Rating<br>(kw) | Hot cupboard<br>(kw) | Bain-marie<br>(kw) | L x W x H<br>(mm) | Weight<br>(kg) | GN 1/1<br>Capacity | Model  |           |
|--|-----------------------|----------------------|----------------------|--------------------|-------------------|----------------|--------------------|--------|-----------|
|  | '`                    | 2.40                 | 0.9                  | 2 x 0.75           | 830 x 680 x 900   | 51             | 2                  | VC2BMW | 1         |
| Base Unit VC3BMW 3 75 1158 x 680 x 900 2 x 1.00 0.9 2.90 3.34 15amp      | 20 3.34 15amp / 20amp | 2.90                 | 0.9                  | 2 x 1.00           | 1158 x 680 x 900  | 75             | 3                  | VC3BMW |           |
|  | 1 Tourney 2 Tourney   | 2.90                 | 0.9                  | 2 x 1.00           | 1486 x 680 x 900  | 101            | 4                  | VC4BMW | No Gantry |
| VC5BMW 5 125 1814 x 680 x 900 2 x 1.00 0.9 2.90 3.78 15amp               | 3.78   15amp / 20amp  | 2.90                 | 0.9                  | 2 x 1.00           | 1814 x 680 x 900  | 125            | 5                  | VC5BMW |           |

## **Gantry options**

Curved glass type, open or closed front with quartz heated and illuminated gantry





| ı | Open Front | Closed Front | Height above top (mm) | Number of 220w<br>lamps | Power Rating<br>(kw) |
|---|------------|--------------|-----------------------|-------------------------|----------------------|
|   | VC2QG      | VC2QGF       | 405                   | 1                       | 0.22                 |
|   | VC3QG      | VC3QGF       | 405                   | 2                       | 0.44                 |
|   | VC4QG      | VC4QGF       | 405                   | 3                       | 0.66                 |
|   | VC5QG      | VC5QGF       | 405                   | 4                       | 0.88                 |

Square glass type, open or closed front with quartz heated and illuminated gantry





| I | Open Front | Closed Front | Height above top (mm) | Number of 220w<br>lamps | Power Rating<br>(kw) |
|---|------------|--------------|-----------------------|-------------------------|----------------------|
| Ι | VC2QG\$L   | VC2QGSLF     | 405                   | 1 1                     | 0.22                 |
|   | VC3QGSL    | VC3QGSLF     | 405                   | 2                       | 0.44                 |
|   | VC4QGSL    | VC4QGSLF     | 405                   | 3                       | 0.66                 |
|   | VC5QG\$L   | VC5QGSLF     | 405                   | 4                       | 0.88                 |

Deli curved or square glass type, closed front with quartz heated and illuminated gantry [Note the shelf is not heated]





| I | Open Front | Closed Front | Height above top (mm) | Number of 220w<br>lamps | Power Rating<br>(kw) |   |
|---|------------|--------------|-----------------------|-------------------------|----------------------|---|
| 1 | VC2QGD     | VC2QGDSL     | 538                   | 1                       | 0.22                 | Ī |
|   | VC3QGD     | VC3QGDSL     | 538                   | 2                       | 0.44                 |   |
|   | VC4QGD     | VC4QGDSL     | 538                   | 3                       | 0.66                 |   |
|   | VC5QGD     | VC5QGDSL     | 538                   | 4                       | 0.88                 |   |

Island curved or square glass type, with quartz heated and illuminated gantry





| I | Open Front | Closed Front | Height above top (mm) | Number of 220w<br>lamps | Power Rating<br>(kw) |
|---|------------|--------------|-----------------------|-------------------------|----------------------|
|   | VC2QGi     | VC2QGiSL     | 405                   | 1                       | 0.22                 |
|   | VC3QGi     | VC3QGiSL     | 405                   | 2                       | 0.44                 |
|   | VC4QGi     | VC4QGiSL     | 405                   | 3                       | 0.66                 |
|   | VC5QGi     | VC5QGiSL     | 405                   | 4                       | 0.88                 |





