

## FEATURES

- Typically can be recharged hundreds of times
- Efficient at high rate discharges
- Significantly higher capacity than nickel-cadmium batteries
- Operates well at a wide range of temperatures:  
Charging 0°C to 50°C and  
Discharging 0°C to 50°C

## RS PRO 12V NiMH Rechargeable Battery Pack, 2Ah

RS Stock No.: 777-0400



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

Rechargeable AA NiMH (nickel-metal- hydride) battery packs from our own brand RS PRO are a great addition to your household.

These Rechargeable Batteries provide approximately 75% of the capacity of alkaline batteries at low drain rates and can surpass alkaline performance in high drain applications (i.e. digital cameras). Even though battery life is limited to 5 years or less, NiMH batteries can be recharged hundreds of times, potentially equivalent to hundreds of alkaline batteries. It's not only convenient but economical as well.

## General Specifications

<b>Chemistry</b>	NiMH
<b>Number Of Cells</b>	10
<b>Terminal Type</b>	Tags
<b>Size</b>	AA
<b>Application</b>	Emergency Lighting; Commercial; Industrial

## Electrical Specifications

<b>Nominal Voltage</b>	12V
<b>Capacity</b>	2000mAh / 0.2CmA
<b>Standard Charge (16H)</b>	0.1CmA for 16hrs
<b>Fast Charge (1H)</b>	1C for 1.2hrs
<b>Trickle Charge</b>	0.03CmA

## Mechanical Specifications

<b>Weight</b>	250g
<b>Relative Humidity</b>	65%

## Operation Environment Specifications

<b>Charge Temperature Range</b>	0°C to 45°C
<b>Storage Temperature Range</b>	-20°C to 35°C

## Approvals

<b>Compliance/Certifications</b>	EN61340
----------------------------------	---------



## Specifications:

<b>Model</b>		AA x 10
<b>Nominal Voltage</b>		12.0 V
<b>Capacity</b>	Typical	2000 mAh/0.2 CmA
	Minimum	1900 mAh/0.2 CmA
<b>Charge</b>	Standard	0.1 CmA for 16 hrs.
	Rapid	1C for 1.2 hrs.(approx.) (With- Δ V, Temp., Time charging control)
	Trickle	0.03CmA (1 month)
<b>Maximum Discharge Current</b>		1 CmA
<b>Discharge Cut-off Voltage</b>		10.0 V
<b>Applicable Temperature</b>	Standard Charge	0°C~+45°C
	Rapid Charge	0°C~+40°C
	Discharge	-10°C~+60°C
<b>Storage</b>	Within one year	-20°C~+35°C
	Within 3 months	-20°C~+45°C
	Within 1 month	-20°C~+55°C
<b>Relative Humidity Range</b>		65%±20%
<b>Weight</b>		Approx. 250 g