

Tenso® LST3-32

Battery Powered Strapping
Tool 25mm - 32mm

#61837



Variable
Tension Speed

Full Touch
User Interface

One Touch
Favourite Setting

Strap Alignment
Indication

The LST3 combination tool delivers high-speed operation and unparalleled performance for plastic strapping applications. Complete with an ergonomic design and multiple performance enhancing features, the LST3 battery hand tool improves productivity for a wide range of applications – from those that require minimal tension to those in heavy industries.

Features

- Full touch user interface
- Variable tension speed
- Favourite strapping function
- Colour display indication for tool status information
- Strap alignment indication
- Strap dust blow out vent
- Battery cover for battery protection




Accessories




User Interface Cover

For additional protection in harsh environments



Protection Plate

For use on abrasive surfaces



Suspension Bow

For stationary applications

Specifications

Operation Mode	auto/semi/manual	BATTERY / CHARGER	
Tension Force Range: Standard Soft	3000 - 7000N 1000 - 5000N	Charger Type	Bosch
Weight (incl. battery)	6.7kg	Battery Charger Voltage	100 or 110 or 230 V
Dimension (LxWxH)	416mm x 157mm x 158mm	Charging Time	70-80 min
Working Temperature	-10°C to +40°C	Battery Type (standard)	Bosch Li-Ion 18V, 8.0Ah
Relative Humidity	up to 90%	Battery Usage Cycle	Up to 450 uses on a single charge (low tension)
Strap Type	PET (Polyester) PP (Polypropylene)		
Strap Width	25mm - 32mm		
Strap Thickness	0.9-1.3 mm		
Joint Type	Friction Weld Seal		