

NLM SERIES LABORATORY REFRIGERATOR

NULINE
REFRIGERATION

FEATURES

- Top Mounted System
- E-Glass and Heated Cabinet Facia to prevent condensation up to 80% R.H.
- Interior Lighting LED
- Automatic Water Disposal
- Digital Display with Built-in Alarms



2°C to 8°C



400 L
700 L
1000 L
1614 L
2170 L



600w x 620d x 1915h
870w x 700d x 2100h
1200w x 700d x 2100h
1880w x 700d x 2100h
2400w x 700d x 2100h

+61 3 9562 3355
info@nuline.au
7 Longford Court, Springvale VIC 3171
www.nulinerefrigeration.com.au



NLM SERIES LABORATORY REFRIGERATOR



MODEL	NLM400/1	NLM700/1	NLM1000/2	NLM1614/3	NLM2170/4
Gross Capacity	400 L	700 L	1000 L	1614 L	2170 L
External Dimensions in mm (w/d/h including castors or legs)	600 x 620 x 1915	870 x 700 x 2100	1200 x 700 x 2100	1880 x 700 x 2100	2400 x 700 x 2100
Internal Dimensions in mm (w/d/h)	500 x 470 x 1435	770 x 550 x 1555	1100 x 550 x 1555	1780 x 550 x 1520	2300 x 550 x 1520
Packed Dimensions in mm (w/d/h including pallet)	700 x 720 x 2065	970 x 800 x 2250	1300 x 800 x 2250	1980 x 800 x 2250	2500 x 800 x 2250
Gross Weight – kg (packed weight)	102	112	137	187	208
Net Weight – kg	95	95	125	175	195
Voltage	240V	240V	240V	240V	240V
Temperature Range	2°C to 8°C	2°C to 8°C	2°C to 8°C	2°C to 8°C	2°C to 8°C
Ambient Temperature Range	10°C to 32°C	10°C to 32°C	10°C to 32°C	10°C to 32°C	10°C to 32°C
Refrigerant	R134a	R134a	R134a	R134a	R134a
Cooling System / Defrost	Fan Forced	Fan Forced	Fan Forced	Fan Forced	Fan Forced
Exterior Cabinet Finish	White Colour-bond	White Colour-bond	White Colour-bond	White Colour-bond	White Colour-bond
Inner Liner Material	White Colour-bond	White Colour-bond	White Colour-bond	White Colour-bond	White Colour-bond
Door	Solid / Glass E-Glass	Solid / Glass E-Glass	Solid / Glass E-Glass	Solid / Glass E-Glass	Solid / Glass E-Glass
Door Hinge	RH	RH	LH / RH	LH / RH / RH	LH / RH / LH / RH
Door Handle	Lockable	Lockable	Lockable	Lockable	Lockable
Type of Controller	Digital	Digital	Digital	Digital	Digital
Temperature Display	External	External	External	External	External
Data Logger	Optional	Optional	Optional	Optional	Optional
Door Ajar Alarms	Optional	Optional	Optional	Optional	Optional
High and Low Readout	Visual / Audible	Visual / Audible	Visual / Audible	Visual / Audible	Visual / Audible
Remote Alarm Contacts (BMS Connectivity for Alarms only) (BMS Connectivity for Temperatures)	Optional Optional	Optional Optional	Optional Optional	Optional Optional	Optional Optional
Port Entry	Optional	Optional	Optional	Optional	Optional
Battery Back-Up For Controller	Optional	Optional	Optional	Optional	Optional
Power Requirement	10amp GPO	10amp GPO	10amp GPO	10amp GPO	10amp GPO
Castors	Yes	Yes	Yes	Yes	Yes
Adjustable Shelves	5	5	5	15	20
Usable Shelf Area in mm (w / d)	480 x 450	750 x 530	1080 x 530	565 x 530	575 x 530
Light	LED	LED	LED	LED	LED

Nuline Refrigeration reserves the right to alter the specifications without prior notice.

NLM SERIES LABORATORY REFRIGERATOR



Since 1985, Nuline Refrigeration has been manufacturing refrigerators and freezer cabinets for the Australian market. Our specialised range of biomedical cabinets are used extensively across the hospitals, medical centres, pharmacies and laboratories.

Focusing on customer needs, we manufacture, import and customise the biomedical cabinets from a range of selected global suppliers. Our factory is based in Melbourne, Australia and we are proudly 100% Australian owned business.

Each of our manufactured cabinets are custom built based on customer orders by our craftsmen right here in Melbourne.

We have extensive capability to design, engineer and build a range of refrigerated cabinets for you. Our standard product range includes, fridges, freezers (up to -40°C), blanket warmer, mortuary refrigerators and refrigerated incubators.

