



TENTE Heavy Duty

Automatically takes the lead
Series 486S/B



Better Mobility. Better Life.

Efficient

Series 468S/B

TENTE-ROLLEN GmbH

Herrlinghausen 75
D-42929 Wermelskirchen
Telefon: +49(0)21 96/99-0
Telefax: +49(0)21 96/99-127
E-Mail: info@tente.de
Internet: www.tente.de

Serie 468S/B – Swivel castor with automatic directional stability



Convenient – No matter what the direction of travel, the auto alignment returns the castor to its zero position when the pallet is raised, and so allowing space-saving storage. The pallet is then immediately ready to move the next time it is needed.



Advantages of the automatic directional stability:

- Support of the directional stability with high speed
- Defined direction of the castor when the castor is raised or in the parking position
- Higher stability

Series 468S/B available as:

- 468S Swivel castor with automatic directional stability
- 468B Swivel castor with automatic directional stability and total lock

Housing:

Housing made of very heavy pressed steel, blue passivated, sealed, swivel double ball bearing

Automatic direction: 180°

Wheel sizes:

Ø 125-250 mm
with hub length 60 mm

Load capacity: up to 800 kg / castors

Fitting:




Plate P62

Plate size: 137 x 105 mm
Plate hole centres: 105/80 x 60 mm
Plate hole: Ø 11 mm

You will find further technical datas on our website: www.tente.de



Fig.: 468S ITP 250 P63



Fig.: 468B ITP 250 P63

Possible wheel combinations:



UAP

Wheel centre: Polyamide, white, Tread: Polyurethane, purple, precision ball bearing, temperature range from -40 to +80 °C



TOO/TOP

Wheel made of Polyamide, white, plain bearing/ precision ball bearing, heavy duty



ITP

Wheel centre: Aluminium, Tread: Polyurethane, casted, flat, precision ball bearing, temperature range from -40 to +80 °C



IEP/IFP

Wheel centre: Aluminium, Tread: Elastic-tyre, grey, non-marking, vulcanized, precision ball bearing, temperature range from -20 to +85 °C

Further wheels can be found in our catalogue 6.2 on page 376 with a hub-length of 60 mm.