



TENTE Heavy Duty

Automatically takes the lead  
Series 486S/B

**TENTE**

BETTER MOBILITY. BETTER LIFE.

# Efficient

## Series 468S/B

### Serie 468S/B – Swivel castor with automatic directional stability



**Convenient** – No matter what the direction of travel, the auto alignment returns the castor to its zero position when the pallet is raised, and so allowing space-saving storage. The pallet is then immediately ready to move the next time it is needed.



Fig.: 468S ITP 250 P63



Fig.: 468B ITP 250 P63

#### Possible wheel combinations:



**UAP**  
Wheel centre: Polyamide, white, Tread: Polyurethane, purple, precision ball bearing, temperature range from -40 to +80 °C



**TOO/TOP**  
Wheel made of Polyamide, white, plain bearing/ precision ball bearing, heavy duty



**ITP**  
Wheel centre: Aluminium, Tread: Polyurethane, casted, flat, precision ball bearing, temperature range from -40 to +80 °C



**IEP/IFP**  
Wheel centre: Aluminium, Tread: Elastic-tyre, grey, non-marking, vulcanized, precision ball bearing, temperature range from -20 to +85 °C



#### Advantages of the automatic directional stability:

- Support of the directional stability with high speed
- Defined direction of the castor when the castor is raised or in the parking position
- Higher stability

#### Series 468S/B available as:

- 468S Swivel castor with automatic directional stability
- 468B Swivel castor with automatic directional stability and total lock

#### Housing:

Housing made of very heavy pressed steel, blue passivated, sealed, swivel double ball bearing

Automatic direction: 180°

#### Wheel sizes:

Ø 125-250 mm  
with hub length 60 mm

**Load capacity:** up to 800 kg / castors

#### Fitting:




Plate P62

Plate size: 137 x 105 mm  
Plate hole centres: 105/80 x 60 mm  
Plate hole: Ø 11 mm