

MC-600C SUCTION UNIT WITH BATTERY

- High vacuum, high flow, oil free vacuum pump
- Antibacterial filter
- Anti-overflow Protection Device
- Lower noise, stepless vacuum adjustment
- Multi-function Deployment Optional
- Three power supply modes: DC battery/DC car battery/AC



Specification:

Max free air flow rate: 20L/min

Max. Vacuum: 0.8bar/600mmHg

Power consumption: \leq 120VA

Display usage: Vacuum meter(model A),

Power source: AC220V(Customizable)/DC12V/Battery

Noise: \leq 55dB(A)

Collection bottle: 1L (Disposable Bag, Collection Jar Optional)

Battery charge/discharge time: 3h/60min

Weight: 6.5kg

Dimensions: 360 \times 180 \times 300mm

MC-600A SUCTION UNIT

- High vacuum, high flow, oil free vacuum pump
- Antibacterial filter
- Anti-overflow Protection Device
- Lower noise, stepless vacuum adjustment
- Multi-function Deployment Optional
- AC Power Supply



Specification:

Max free air flow rate: 20L/min

Max. Vacuum: 0.8bar/600mmHg

Power consumption: \leq 120VA

Display usage: Vacuum meter(model A)

Power source: AC220V(Customizable)/DC12V/Battery

Noise: \leq 55dB(A)

Collection bottle: 1L (Disposable Bag, Collection Jar Optional)

Battery charge/discharge time: 3h/60min

Weight: 4.3 kg

Dimensions: 360 \times 180 \times 300mm