

Mesh Bag Packaging Machine for Vegetable and Fruit

BU Series

Optional device

- Hanger hole punch device
- Film splice assist units
- Material stopper
- Safety device
- Bag support

Film type

- PE-net
- Film-net combination



Model	BU-620	BU-800	BU-1000	BU-1200
Film width	240-620mm	340-800mm	500-1000mm	600-1200mm
Bag length	70-380mm	100-480mm	100-600mm	100-800mm
Speed	Max. 25 bpm	Max. 20 bpm	Max. 15 bpm	Max. 10 bpm
Power supply	220V, 50/60HZ, 3KW	220V, 50/60HZ, 4KW	220V, 50/60HZ, 5KW	220V, 50/60HZ, 6KW
Air requests	0.36m ³ /min, 0.6Mpa	0.4m ³ /min, 0.6Mpa	0.6m ³ /min, 0.6Mpa	0.8m ³ /min, 0.6Mpa
Outer dimension	1600x1260x1680mm	1600x1500x2050mm	2170x1780x2740mm	2170x1780x3040mm

Inclined Vertical Packaging Machine

BD Series

Optional device

- Nitrogen gas flushing
- Hole punch device
- Tear notch device
- Static eliminator
- Thermal transfer printer

Application

Fragile products such as biscuits, pastries, baked goods, brittle products in general.



Model	BD-500	BD-620
Film width	180-500mm	240-620mm
Bag length	60-300mm	70-380mm
Speed	Max. 65 bpm	Max. 60 bpm
Power supply	220V, 50/60HZ, 4KW	220V, 50/60HZ, 4.5KW
Air requests	0.4m ³ /min, 0.6Mpa	0.4m ³ /min, 0.6Mpa
Outer dimension	1880x1250x1220mm	2150x1260x1350mm