

## ChemGrout CGMIX22 Paddle Mixer

- The ChemGrout CGMIX22 is a paddle mixer equipped with a vertical shaft and features specially designed blades and baffles to develop a high shear mixing action, insuring a rapid and thorough mix.
- The paddle rotates at speeds up to 200 RPM.
- The tank bottoms are sloped toward the outlet slide valve so the thickest materials fall easily into the pump hopper.
- Each mixer is equipped with baffles, bag breakers , covers and variable speed high-efficiency paddles that provide a rapid mixing cycle.
- The MIX22 paddle mixer has a 80 litre capacity and is available in a wide variety of power options including: Air, Hydraulic and Electric with a variable frequency drive for speed control.
- The tank leg height can be specified to meet your jobsite conditions.
- The rugged steel frame stands up to the toughest conditions on the jobsite.
- Operator controls are centrally located for efficient production.
- All components are easily accessible for operating, cleaning and maintenance.



CGMIX22	Requires	Weight	Size (L x W x H)
Air	Air Powered Pneumatic Mixer Requires 60 CFM, 100 PSI of compressed air	95kg	86.4 x 71.1 x 119.4cm
Hydraulic	Hydraulic Powered Mixer Requires 12 GPM, 1000 PSI of hydraulic oil	88kg	86.4 x 71.1 x 119.4cm
Electric	Electric Powered Mixer Single or Three Phase Power	95kg	86.4 x 71.1 x 119.4cm