



REINVENT HOW THE WORLD CLEANS



# T981

## Ride-on floor scrubber

### Maneuverable and productive

T981 effectively scrubs and dries large hard-floor surfaces with light to medium dirt and stains. Its intuitive controls make it easy to operate and maintain. T981 is ideal for cleaning smooth floors in areas such as retail, logistics and light industry.



### Productivity boost

Easily fit into the most congested spaces with narrow turning radius and get more cleaning done with the lead acid batteries that allow cleaning shifts up to 4.6 hours.



### Simple operation

Easy start-up and quick training with three pre-set cleaning programs that allow operator to choose whichever program best fits their soil level.



### Get the right solution

Choose between the 90 cm disk or 75 cm cylindrical scrub deck to fit T981 into your application.

# Inside the T981

- 1. Easily change water flow rate** and other cleaning functions from intuitive control panel.
- 2. Enhance facility image and safety** by recovering more water with high-performance 3-stage vacuum motor.
- 3. Quick, mess-free tank draining** with large, pinch-style recovery tank drain hose.
- 4. Large solution tank** with level gauge and drain hose.
- 5. Consistent water pick-up** with durable parabolic squeegee design and standard Linatex® squeegee blades.
- 6. Simple no-tools, no-touch brush change** system.



## T981 specifications

FEATURE	SPECIFICATION	
	DISK	CYLINDRICAL
Cleaning path	900 mm	750 mm
Productivity theoretical max	5,300 m <sup>2</sup> /hr	4,300 m <sup>2</sup> /hr
Estimated coverage*	3,950 m <sup>2</sup> /hr	3,100 m <sup>2</sup> /hr
Scrubbing speed	6 kmh	
Scrub head and squeegee raise/lower	independent actuators	
Brush speed	200 rpm	1000 rpm
Brush pressure	100 kg	50 kg
Solution tank capacity	125 L	
Recovery tank capacity	135 L	
Battery run time - up-to hours (240Ah Gel Battery)**	4.6	
Battery voltage	6 x 6V	
Dimensions (LxWxH)	1,720 x 1,100 x 1,360 mm	1,810 x 1,050 x 1,360 mm
Squeegee width	1,100 mm	1,010 mm
Weight (with heaviest battery)	707 kg	715 kg
External radius (wall to wall)	2,310 mm	2,430 mm
Maximum climbing angle	9° / 16%	
Sound level (operator's ear)***	72 dBA	

Specifications subject to change without notice.

\* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

\*\* Run times are based on Continuous Scrubbing Run Times.

\*\*\* Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA

For a demonstration or additional information, call **1800 226 843** or email [contactus@tennantco.com](mailto:contactus@tennantco.com)

T981-brochure-en-au 8/24

©2024 The Tennant Company logo and other trademarks designated with the symbol "®" are trademarks of Tennant Company registered in the United States and/or other countries. Tennant Company's products are sold and serviced through subsidiaries of Tennant Company and distributors. All rights reserved.

**Tennant Australia**  
 Unit 2, 10 Johnston Crescent  
 Horsley Park NSW 2175  
 T: 1800 226 843 (FREE CALL)  
 T: +61 2 9839 9700  
[www.tennantco.com.au](http://www.tennantco.com.au)  
[contactus@tennantco.com](mailto:contactus@tennantco.com)

**Tennant New Zealand**  
 18 Onslow Ave, Papatoetoe,  
 Auckland, 2104  
 T: +64 9 253 9013  
 F: +64 9 253 9015  
[www.tennantco.co.nz](http://www.tennantco.co.nz)  
[contactus@tennantco.com](mailto:contactus@tennantco.com)