

BROOKS

EQUIPMENT

Phone: 1300 276 657

Email: service@brooksequipment.com.au

www.brooksequipment.com.au

ISO 14001

BUREAU VERITAS
Certification



AS/NZS 4801

BUREAU VERITAS
Certification



ISO 9001

BUREAU VERITAS
Certification



Italdem is one of the most well-known brands of hydraulic hammers in production on the Italian market and is also one of the most competitive in the industry worldwide. We produce high-quality tools that are ready to work in the hardest working conditions, with proved durability and low maintenance. This is the result of more than 30 years of experience.



MANUFACTURERS OF
HYDRAULIC HAMMERS



The ITALDEM GK series offers the best solution for all kinds of demolition jobs. A comprehensive range of powerful and precisely working breakers as the result of modern technology and first class material. ITALDEM GK, the brand for demolition at its best.



GK 4000 S GK 3000 S GK 2500 S GK 1810 S GK 1560 S GK 1360 S GK 1060 S

OPERATING WEIGHT	4000 kg	3000 kg	2400 kg	1800 kg	1500 kg	1350 kg	1050 kg
TOOL DIAMETER	185 mm	165 mm	150 mm	140 mm	132 mm	120 mm	114 mm
OIL FLOW	300-310 l/min	250-260 l/min	220-230 l/min	200-210 l/min	160-170 l/min	150-160 l/min	130-150 l/min
WORKING PRESSURE	150-160 bar	150-160 bar	140-150 bar	140-150 bar	140-150 bar	130-140 bar	110-120 bar
RELIEF VALVE	200 bar	200 bar	200 bar	200 bar	200 bar	200 bar	170 bar
MAX. BACKPRESSURE	12 bar	12 bar	12 bar	12 bar	12 bar	12 bar	12 bar
BLOW ENERGY	8300 joule	6300 joule	5000 joule	4400 joule	3500 joule	3000 joule	2300 joule
REQUIRED POWER	112 hp	93 hp	78 hp	70 hp	56 hp	50 hp	38 hp
IMPACT RATE	450 (600)	500 (640)	550 (700)	550 (700)	580 (700)	600 (750)	500-600
CARRIER WEIGHT	40-65 t	30-50 t	28-40 t	22-30 t	20-28 t	18-25 t	13-20 t
MAX. NOISE LEVEL (SILENCED VERSION)	88 db-A	88 db-A	88 db-A	88 db-A	88 db-A	88 db-A	88 db-A
INNER DIAMETER HP LINE	32 mm	32 mm	32 mm	26 mm	26 mm	26 mm	20 mm
INNER DIAMETER LP LINE	38 mm	38 mm	38 mm	38 mm	38 mm	38 mm	36 mm



Contact
 Nathan Fenemer - 0438 631 952
nfenemer@brooksequipment.com.au



The ITALDEM GK series offers the best solution for all kinds of demolition jobs. A comprehensive range of powerful and precisely working breakers as the result of modern technology and first class material. ITALDEM GK, the brand for demolition at its best.



GK 630 S **GK 450 S** **GK 320 S** **GK 225 S** **GK 165 S** **GK 100 S** **GK 75 S** **GK 19**

OPERATING WEIGHT	650 kg	450 kg	330 kg	220 kg	155 kg	105 kg	75 kg	19 kg
TOOL DIAMETER	105 mm	85 mm	80 mm	67 mm	56 mm	46 mm	40 mm	25 mm hex
OIL FLOW	110-130 l/min	75-100 l/min	45-85 l/min	35-60 l/min	25-40 l/min	15-30 l/min	13-25 l/min	15-30 l/min
WORKING PRESSURE	110-120 bar	105-115 bar	95-105 bar	95-105 bar	95-105 bar	95-105 bar	95-105 bar	150 bar
RELIEF VALVE	170 bar	150 bar	140 bar	140 bar	140 bar	140 bar	140 bar	170 bar
MAX. BACKPRESSURE	12 bar	12 bar	12 bar	12 bar	12 bar	12 bar	12 bar	17 bar
BLOW ENERGY	1700 joule	1050 joule	750 joule	520 joule	350 joule	200 joule	160 joule	70 joule
REQUIRED POWER	35 hp	25,5 hp	20 hp	14 hp	9.5 hp	7 hp	6 hp	4,5 hp
IMPACT RATE	600-650	650-900	540-1000	620-1050	670-1050	700-1350	750-1430	800-1600
CARRIER WEIGHT	9-15 t	7-11 t	4,5-9 t	3-6 t	2-4,5 t	1-3 t	0,5-2 t	manual
MAX. NOISE LEVEL (SILENCED VERSION)	88 db-A	90 db-A	90 db-A	90 db-A	90 db-A	93 db-A	93 db-A	105 db-A
INNER DIAMETER HP LINE	20 mm	20 mm	20 mm	20 mm	16 mm	16 mm	16 mm	13 mm
INNER DIAMETER LP LINE	36 mm	30 mm	30 mm	26 mm	20 mm	20 mm	20 mm	13 mm



Contact
 Nathan Fenemer - 0438 631 952
nfenemer@brooksequipment.com.au



The ITALDEM GK series offers the best solution for all kinds of demolition jobs. A comprehensive range of powerful and precisely working breakers as the result of modern technology and first class material. ITALDEM GK, the brand for demolition at its best.

GF - CRUSHER BUCKET



GV - SCREENING BUCKET



	GF10	GF20	GF35	GF45	GV 1500
WEIGHT	1200 kg	1900 kg	3500 kg	4500 kg	1600 kg
HEIGHT	1020 mm	1291 mm	1432 mm	1478 mm	1790 mm
WIDTH	880 mm	886 mm	1080 mm	1424 mm	1560 mm
LENGTH	1635 mm	1903 mm	2713 mm	2775 mm	2385 mm
FEEDER DIMENSIONS	590x370 mm	600x500 mm	800x700 mm	900x700 mm	-
OUTPUT SIZE	30-130 mm	30-150 mm	30-150 mm	30-150 mm	-
SAE VOLUME	0,35 m3	0,5 m3	0,7 m3	1 m3	0,8 m3
CARRIER WEIGHT	7,5-13 t	13-18 t	20-28 t	28-40 t	13-25 t
INNER DIAMETER HP HOSE	19 mm	20 mm	20 mm	20 mm	20 mm
INNER DIAMETER LP HOSE	19 mm	30 mm	30 mm	30 mm	26 mm
HP THREAD	3/4" GAS	1" GAS	1" GAS	1" GAS	1" GAS
LP THREAD	3/4" GAS	1" GAS	1" GAS	1" GAS	1" GAS
OIL FLOW	100-105 l/min	110-115 l/min	150-160 l/min	150-160 l/min	80-100 l/min
WORKING PRESSURE	180-200 bar	180-200 bar	180-200 bar	180-200 bar	100-210 bar



Contact
 Nathan Fenemer - 0438 631 952
nfenemer@brooksequipment.com.au