





The HW-1310 is compact and easy to move making it the ideal hot water system for those not operating in the industrial sector.

The high temperatures coupled with a pressure of 2030 psi and 9L/pm flow means this hot water blaster breaks down dirt and greases quickly and easily so you can get on with your day.

Features

- · Brass pump head pump with ceramic pistons
- · Delayed Total Stop System
- ATC Temperature System
- Water leakage intelligent shutdown protection
- Dry Run Protection
- Nozzle blockage intelligent shutdown system
- Anti Corrosion Coated Boiler Coil
- · 4 wheel heavy duty chassis
- Boiler ignition delay
- · Adjustable Pressure
- Pressure Gauge

Standard Accessories M22 Handgun, 10m High Pressure Hose, 50cm Double lance with LP nozzle

Optional: Hose Reel

Specifications	Detail/ Benefit
Dimensions (L x W x H)	820mm x 630mm x 870mm
Weight (Gross)	75Kg
Operating Pressure	40-140 bar/ 600-2030 psi
Flow	9 l/min
Max Output Temperature	30-130 deg C
Input Power Requirement	Single Phase 230V, 12A (15A Plug)
Pump Type	Linear Triplex crank driven
Motor/ Pump Speed	Induction 2800rpm
Bypass System	Separate Brass unloader

Specifications	Detail/ Benefit
Burner Fuel Tank Capacity	18L
Burner Heating Capacity	37.8 kW
Burner Fuel Conspumption	3.2kg/h
Detergent Tank Capacity	2L
Detergent System	Low Pressure
Sound Pressure Level	78 dB(A)
Warranty	Machine 12 Months, Boiler Coil 2 Years, Accessories 3 Months