



URL: <https://www.foodequipment.com.au/media/catalog/product/p/t/ptd-601d.jpg>

Axwood Passthrough Dishwasher 3 phase - PTD-601D

Quick Overview

Axwood Pass-Through Dishwasher - Hood Type Dishwasher - PTD-601D

- Easy to use: Easy installation and service
- User- friendly one touch system
- High Performance: Powerful wash pump deliver higher volumes of wash water and ensures faster clean up times.
- Low running costs: Hi- tech computer controller ensures low water, low energy and less detergent consumption.
- Quality: Full stainless steel structure with stainless steel wash & rinse arms.
- Incoming water temperature 10-60Å ° C
- WaterMark approved

Description

Axwood Pass-Through Dishwasher - Hood Type Dishwasher - PTD-601D

- Easy to use: Easy installation and service
- User- friendly one-touch system
- High Performance: Powerful wash pump delivers higher volumes of wash water and ensures faster clean up times.
- Low running costs: Hi-tech computer controller ensures low water, low energy, and less detergent consumption.
- Quality: Full stainless steel structure with stainless steel wash & rinse arms.
- Incoming water temperature 10-60Å ° C
- Rated currently of air circuit breaker 40A
- Record the number of washing 9999
- 60 racks per hour
- Drain outlet 42mm
- WaterMark approved

Specifications

- Net Weight: 104kg
- Dimensions (WxDxH): 710 x 790 x 1430 ± 20 mm
- Door Entry: 400mm
- Basket Size: 500 x 500mm
- Electrical Supply (V/Hz/ph): N?415V AC / 50Hz / 3ph
- Cycle Length(3wash cycles): 60 / 90 / 120 sec

Wash Pump, Tank and Element

- Wash Pump: 3-ph:400 L/min, 0.6 Kw
- Wash Tank Capacity: 27 Litres
- Wash Tank Heater :3.0 Kw
- Wash temperature: 60 ° C to 65 ° C

Rinse Pump, Tank and Element

- Rinse Pump: 0.35 Kw
- Rinse Tank Capacity: 11 Litres
Rinse Tank Heater: 9Kw
- Rinse Temperature: 82 ° C minimum
- Water Consumption: 2.9 Litres per cycle

Electrical and Water Connections:

- Electrical Input: 415V / 50Hz / 3ph, 15.71Kw
- Water Input: 15 ° C minimum @ 100-400kPa
- Hot Water Inlet: 3/4 " B.S.P. fitting
- Drain Outlet: 1 1/2 " B.S.P. gravity fed

1 Year Parts and Labour Warranty

Your Shipping Specifications

Net Weight (Kg)	104
Width (mm)	710
Depth (mm)	790
Height (mm)	1430
Packing Width (mm)	850
Packing Depth (mm)	745
Packing Height (mm)	1600
Power	415V / 50Hz / 3ph, 15.71Kw