

Paxum® X200

Fully Automatic
Stretch Wrap Machine
With Power Pre-stretch Head &
Remote Control



Paxum Wrapping Solutions

Features

- High efficiency and low energy consumption
- Remote Controlled System
- Automatic Photoelectric sensor detects pallet height
- Automatic film cutter
- Multi-layer function: This function can set different wrapping cycles and wrapping tension at any height, up to 9 layers per pallet.
- 400% pre-stretch film rate.
- Advanced Safety Technology
 - Safety device under film carriage to protect the foot or head of the operator
 - Transparent panel makes it easy to find problem without opening door.
 - Up and down belt deviation and damaged alarm system
- High quality electrical components
- LCD Touch Operating System
- Automatic Rope Grip System
- Soft start and soft stop.
- Intelligent Alarm system with LED Indicator
- 1800mm turntable
- 2350mm wrapping height
- Max load weight: 2000KG
- 5 Year Warranty

Specifications

| | |
|----------------------|--|
| Production Rate | 30-40 loads/hour |
| Turntable Speed | 3-12RPM(Adjustable) |
| Turntable Diameter | 1800mm |
| Max. Load Weight | 2000kgs |
| Std. Wrapping Height | 2350mm |
| Pre-stretch Rate | 400% pre-stretch maximum |
| Up & Down Speed | 1.5 ~5.5 m/mins |
| Voltage | 240V |
| Machine weight | 750kg |
| Machine size | L2710mm*W1800mm*H2740mm |
| Film Spec. | 500mm wide, 250mm diameter, 76mm core diameter |
| PLC | Siemens |
| Compressed Air | Yes |
| Technical Data | Operation Manual |
| Extra Options | Weighing Scales Ramp |
| Warranty | 5 Years |

