



# Veva Sirius G2

## Asymmetrical Area Floodlight

---



**EarthLight**  <sup>TM</sup>  
TRADE

Industrial & Commercial Lighting  
[earthlight.com.au](http://earthlight.com.au)

# Veva Sirius G2

## Asymmetrical Area Floodlight

The state-of-the-art VEVA Sirius Gen2 floodlight has arrived – higher performance, lighter weight and improved optics, engineered for high mast and area flood lighting. Available from 60 to 1800W, making it ideal for billboards, signage, facade and sports field, court or stadium lighting.

**Great Performance with  
a Slim Profile**

- ✓ Slim Profile Offering The Best Performance Ratio for Wind Resistance and Weight
- ✓ Versatile Sports And Area Flood Lighting, with System Efficacy Up To 140 Lm/W
- ✓ IP67 Rated for High Water and Dust Resistance
- ✓ Unique Heatsink Technology for Greater Thermal Performance
- ✓ 7 Year Warranty



earthlight.com.au  
1300 410 485  
sales@earthlight.com.au

# Veva Sirius G2

## Specifications

| CODE               | ETG-02VS012 | ETG-02VS014 | ETG-02VS016 | ETG-02VS018 | ETG-02VS019 |
|--------------------|-------------|-------------|-------------|-------------|-------------|
| LED Power (W)      | 100W        | 200W        | 300W        | 400W        | 500W        |
| Luminous flux (lm) | 14,100      | 31,300      | 44,100      | 62,600      | 71,200      |
| Weight (Kg)        | 5.9         | 8.2         | 11.1        | 12.3        | 21.5        |

| CODE               | ETG-02VS020 | ETG-02VS021 | ETG-02VS022 | ETG-02VS023 | ETG-02VS024 |
|--------------------|-------------|-------------|-------------|-------------|-------------|
| LED Power (W)      | 600W        | 800W        | 1000W       | 1200W       | 1500W       |
| Luminous flux (lm) | 88,200      | 125,300     | 142,400     | 170,800     | 202,500     |
| Weight (Kg)        | 22.2        | 30.1        | 31.5        | 35.5        | 35.5        |

|                  |                                      |  |  |  |  |
|------------------|--------------------------------------|--|--|--|--|
| Driver           | Inventronics                         |  |  |  |  |
| CCT              | 4000K (Optional 3000K, 5000K, 6500K) |  |  |  |  |
| Lumen Efficiency | 60° x 60°                            |  |  |  |  |
| Lens Material    | Tempered glass                       |  |  |  |  |
| Finish           | Aluminium                            |  |  |  |  |
| Bracket          | Stainless steel                      |  |  |  |  |
| IP Rating        | IP67                                 |  |  |  |  |
| Warranty         | 7 years                              |  |  |  |  |



