# Paxum® X300

Paxum Fully Automatic Pallet Wrapping Machine

#62217

With Top Pressure Plate



PLC Control / Manual Option

Advanced Technology High Efficiency Remote Control
Operation





Welcome to the innovative Paxum X300 Fully Automatic Pallet Wrapping Machine. The X300 provides consistent pressure on your goods whilst wrapping with the Motor Drive Top Plate, ensuring secure packaging. Our machine uses high-quality Paxum Machine Stretch Film, providing excellent load stability and containment during transportation and storage.

# **Highlights**

#### • Top Pressure Device:

Our industrial-grade Electric Pressurizing System ensures stability and prevents scattering and displacement during the wrapping process. With a pressurizing stroke of 500mm-2000mm, it is suitable for a wide range of applications.

#### Automatic cut and clamp film:

The Paxum X300 Automatic Cut and Clamp Film System eliminates the need for manual film cutting and application on pallets. It automatically cuts and clamps the film, saving time and effort for workers. Say goodbye to manual film handling.

#### • SIEMENS control system:

When investing in a reliable and durable machine, the quality of its electrical components becomes crucial. Using inferior electrical parts poses a significant risk, as a malfunctioning component can halt the entire machine's operation. Repairing electrical issues can also be challenging, as identifying the specific faulty part is often complex. That's why our pallet stretch wrapping machines exclusively utilize renowned brands for all electrical parts. We prioritize the seamless functionality of our machines to ensure long-lasting and trouble-free operation.

## • LCD touch operating system:

Paxum X300 pallet wrapping machines feature state-of-the-art IoT intelligent touch screens that offer flawless responsiveness and functionality. The touch screen allows direct adjustment of turntable speed, up/down speed, and film carriage speed. We provide six pre-set wrapping models to accommodate various pallet types, eliminating the need for frequent parameter adjustments. Simply select the appropriate model for your pallet, streamlining the wrapping process.

## • Remote control system:

Our machine offers convenient remote-control operation, allowing for easy start and pause functions. Each remote control is dedicated to controlling a single device, ensuring simplicity and efficiency in operation.



**Top Pressure Device** 



**Automatic Cut & Clamp** 



**Remote Control Operation** 

### **Features**

- High efficiency, low electricity consumption, easy operation
- Customizable wrapping type and frequency
- Automatic pallet height detection with photoelectric sensor
- Auto reset of turntable
- 300% pre-stretch ratio for optimal film usage
- Programmable control with optional frequency converter
- PLC control with manual option
- Adjustable wrap cycle (top, bottom, reinforcement)
- Variable lift speed and film tension control
- Automatic film cutting and clamping
- Remote control for convenient machine start
- 3 Year Warranty

# **Specifications**

Maximum wrapping speed 15-25 loads/hour 2200mm **Max Wrapping Height** 2000KG **Max Wrapping Weight** 

0-13RPM(Adjustable) **Turntable Speed** 

Turntable Size 1650mm

**Turntable Drive** 0.75PH Chain Drive

**Cut And Clamp Film** Automatic

L:2800mm W:1650mm H:3250mm **Machine Size** 

**Machine Weight** 800KG

**Standard Pre-Stretch** 300% pre-stretch 250mm Diameter **Film Capacity** 

500mm Standard Film Width

Film Delivery System Power Pre -Stretch

**Packing Force** Changeable Intelligent-Sensor Standard **Rope Grip System** Optional **Safety Device** CE standard

Available

**Alarm System** 

Ramp

**Top Pressure** Motor Drive/600 2200mm

press height optional

Steel+ABS Frame **Printing** Metallic Pain Fall-proof Inside Safety Belt

**Cutting** Laser Turntable Roller Double Nylon Roller

**Up & Down Drive** Belt

Up & Down Guideway Double Balance Device

Inverter SIEMENS

Photoelectric sensor SICK(Germany)

PLC SIEMENS (Germany)

OMRON(Japan) **Travel Switch** GPG(Taiwan) Motor

OMRON(Japan) Relay

Reducer GPG

**Position switch** SICK(Germany) X-LINE/SIEMENS Touch screen

Contactor SIFMENS Warranty 3 Years

