

Nordfab Pty Ltd Wet Spray Booths

Nordfab WET SPRAYBOOTH SERIES

Description

The Nordfab range of Wet Spray booths is constructed from bolt-together sheet metal panels. Filtration is achieved by a recirculating water wall. The wet type system is suitable to filter many paint and adhesive products. Spray booths are supplied complete with axial extraction fan(s).

Operating Principle

The operator positions the object to be sprayed within the confines of the booth. Fresh air is drawn in through the front opening of the booth causing the over spray to be caught in the filter. The cleaned air is discharged out through the plenum behind the filter wall and out through a discharge duct.

Construction

1mm and 2mm thick Powdercoated sheetmetal construction.

Filters

Recirculating water wall.

Applications

Spray painting (all paint types)
Adhesive spraying
Vanishing

- **Suitable for a range of applications**
- **High filtering efficiency**
- **Designed according to AS4114**
- **Fluorescent lighting**



Model	Water Curtain Width (mm)	Overall Width (mm)	Overall Height (mm)	Overall Depth (mm)	Airflow (L/s)
SBW25	2500	2800	2550	2200	3200
SBW30	3000	3300	2550	2200	3900
SBW45	4500	4800	2550	2200	5800
SBW60	6000	6300	2550	2200	7700