

DF-770 PORTABLE SUCTION PUMP

General Purpose Medical Suction Series



THE NEW EASY TO CARRY SUCTION PUMP FOR ALL-ROUND USE.



OFFICE AND SHOWROOM:

23/9-15 Sinclair St, Arundel QLD 4214

Phone: (07) 5529 0753 or Free Call: 1800 677712

General enquiries: sales@medeleq.com.au

Shop online now www.medeleg.com.au/Store

Distribution all States

Portable Suction Unit **DF-760**

The Portable Suction Unit provides reliable high vacuum for a variety of applications in hospitals, clinics and medical practices. The DF-770 is a truly innovative and uniquely designed medical suction unit, offering new standards of hygiene, ease of use and low noise levels.

Benefits

- The outer shell is made by ABS plastic injection.
- Easy to transport due to light weight and carrying handle.
- The built-in type collection bottle design saves more space.
- The PC collection bottle may prevent high heat and also autoclavable.
- The capsule shaped floating control can fully prevent overflow by any angles.
- The angle pipe may lead the fluid in smoothly.
- Simplicity of design to enhance safety and hygiene
- The fan installed at the back of the machine helps to prevent the heat.

Standard Accessory

Suction tube (S)	180cm	1PC
Suction catheter		1PC
Filter (S)		2PCS

Specification

Vacuum range	> 650 mmHg
Max. flow rate	40 L/min
Capacity	1500 c.c.
Safety device	Floating control (S)
N.W. / G.W.	5 / 6.2 kg
Machine size	L34 x W17 x H40 (cm)
Packing size	L37 x W25 x H35.5 (cm)




The cooling fan and dual-fuse device design.



Built-in type collection bottle.



The inlet holes of VACUUM side and PATIENT side are marked by color.
RED - VACUUM
GREEN - PATIENT



The capsule shaped floating control may fully prevent overflow by any angles.
The angle pipe may lead the fluid in fluently.

Filter (S)

L type adaptor (green)

Angle pipe (S)

Safety device (S)

1500 c.c. PC bottle

Vertical adaptor (red)

Vacuum gauge

Power switch (ON/OFF)

Regulator valve



Disposable Liners or Reusable Collection Jar

90-016 Oil-less Piston Vacuum Pump



Thermal protector, auto reset.

Pump specification

Voltage	120V / 240V
Current	0.9A / 0.45A
Capacitor	5uf / 2uf
R.P.M.	1720 rpm
Output	90W
Max. flow rate	40 L/min
Vacuum range	> 650 mmHg
Weight	2.6 kg