







-  AUSTRALIAN DESIGNED
-  FUEL EFFICIENT
-  CUSTOMISABLE
-  DURABLE

Powered by



PRODUCT SPECIFICATIONS

GENERAL

Model	GP1100C
Power Type	Diesel
Prime Power (kW/kVA)	800/1000
Standby Power (kW/kVA)	880/1100
Rated Current	1391AMPS
Operating Ambient Temp.	50°C

ENGINE

Engine Model	Cummins KTA38-G5
Aspiration	Turbocharged and aftercooled
No. of Cylinders	12
Governor Type	Electronic Governor
Lubricating Oil Capacity	135.1L

ALTERNATOR

Model	GP404J1
Frequency	50/60
Rate Power (kW/kVA)	824/1030
Power Factor	0.8
Exciter Type	PMG
Voltage Regulator	MX321
Voltage Regulation	±0.5%
No. of Phases	3
Insulation	Class H
Protection	IP21
Altitude	1000m

UNIT

Dimensions (LxWxH)	5800 x 2250 x 2580
Dry Weight	12000kg

FUEL CONSUMPTION

Fuel Consumption*	161(L/h)
Fuel Tank Capacity	Without fuel tank

NOISE LEVEL

Sound Pressure at 7m/dB	85
-------------------------	----

SAFETY FEATURES

ISO Compliant
Outlet package with AS3000 compliant RCD protection
Emergency E Stop

CONTROL SYSTEM

Operator friendly DSE control system

ENCLOSURE FEATURES

Sound attenuated canopies
Powder coated finish
IP65 rating
Fully bunded extended run fuel tanks

WARRANTY

12 months warranty, further options available

OPTIONS

3 way fuel valves
Multiple synchronization of units
Load share capabilities

*Fuel consumption based on 75% load