

Pizza — TP3 C SP TN EP

Catering



Technical data

Gross volume	609 lt
Working temperature	0+8 °C
Motor type	Remote
Refrigerant	R452A
Refrigeration power	482 W (-10°C / +45°C)
Absorption	204 W
Voltage/Frequency	230V/1~/50Hz

Refrigeration details

Refrigeration unit	Remote with possibility to get as optional protection cover
Evaporator	With cataphoresis anti-corrosion treatment
Defrost	Automatic by air
Condensate evaporation	Automatic by electric heater

Construction details

Product dimensions WxDxH	2500x800x860
Packaging dimensions WxDxH	2550x850x1000
Gross weight	177 Kg
Worktop	Without worktop
Structure	Stainless steel AISI 304 monocoque
External/Internal material	Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel
Insulation thickness	60 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP)
Inner corners	Rounded for an easy cleaning
Door	3 Self-closing doors with 105° door stop, reversibles on site
Door gasket	Magnetic and removable, designed to improve insulation and to reduce energy consumption
Feet	AISI 304 stainless steel, height adjustable (135mm-230mm)

Functions

Control panel	Compact, simple and intuitive touch screen display. Tilted control panel
---------------	--

Accessories

No. included accessories	3 - Plastic-coated grid EN 600x400 mm 3 - Pair of runners for grid EN 600x400 mm
--------------------------	---

Remote unit data

Refrigerant gas for remote motor unit	Set up for R452A
---------------------------------------	------------------

Versions

Versions	Power supply frequency 60Hz
----------	-----------------------------