

COMMERCIAL DRYER (REAR CONTROL) FOR ON-PREMISES LAUNDRY APPLICATIONS

w: aqualogic.com.au/contact

CD9E - CD9G 8,2 KG

FEATURES

- · Superior airflow
 - Advanced blower system produces airflow of 220 cu. Ft. per minute
 - Fast-drying results with advanced airflow pattern
 - Minimum dry time
- Large capacity
 Large 7.0 ct ft. cylinder
- Door opening of 2.06 sq. ft. for fast and easy loading and unloading
- Time savings
 Large, easy-clean lint filter is located upfront

CONTROL

· E-Mech control

The E-Mech Control on IPSO dryers assures reliable performance and helps optimize efficiency. The control panel offers convenient features - including on energy-saving cycle with an electronic timer.

Push-to-Start button
 Features simple, push-to-start activation with an 'In Use' LED light



	CD9E	CD9G
MODEL NUMBER	BDEMNRGS433AW01	BDGMNRGS303AW01
CONTROL	Hybrid Emech	Hybrid Emech
CONTROL LOCATION	rear	rear
DRUM		
CAPACITY (KG)	8,2	8,2
CYLINDER VOLUME (L)	198	198
MOTOR		
POWER (KW)	0,25	0,25
CABINET		
CYLINDER FINISH	galvanized	galvanized
COLOUR	white	white
DOOR TYPE	solid	solid
HEATING		
HEAT SOURCE	electric	gas
HEATING POWER	4000 kW	25 000 BTU
CONNECTION		
GAS INLET CONNECTION (MM)	n/a	9,5
EXHAUST OUTLET DIAMETER (MM)	102	102
EXHAUST AIRFLOW (LITERS/SEC)	105	105
OPERATION		
CYCLES	4	4
CYCLE INDICATOR LIGHTS	no	no
POWER		
ELECTRICAL REQUIREMENTS	240V / 50Hz / 1Ph	240V/50Hz/1Ph
TRANSPORT DATA		
GROSS WEIGHT (KG)	73	73
NET WEIGHT (KG)	68	68
DIMENSIONS H X W X D (MM)	1092 x 683 x 711	1092 x 683 x 711
PACKING DIMENSIONS H X W X D (MM)	1156 x 762 x 864	1156 x 762 x 864
VOLUME (m³)	0,76	0,76

^{*} heights may slightly vary, depending on the leveling adjustments



