



Features:

- Top Mounted System
- TGA Approved
- Cabinet Finish In Stainless Steel Interior/Exterior
- Automatic Defrost And Water Disposal
- 5 Adjustable Shelves Per Door
- Available in Glass Door (TNG) or Solid Door (TN)
- Digital Display with Built In Alarms
- Hi / Lo Read Out



Temperature




10°C to 40°C

Capacity



MFi70TN 700L



Dimensions

MFi70TN 725w x 830d x 2010h

Specifications

Optional equipment



Temperature
Data Logger

Keypad

Model	MF170TN	MF170TNG
Capacity	700 L	700 L
External Dimensions	725w x 830d x 2010h	725w x 830d x 2010h
Internal Dimensions	585w x 650d x 1430h	585w x 650d x 1430h
Weight	110 Kg	132 Kg
Voltage	240 V	240 V
Watts	385 W	385 W
Power Requirement	10 amp GPO	10 amp GPO
Refrigerant	R134a	R134a
Warranty	12 Months*	12 Months*
Shelves size	530 x 640	530 x 640
Number of Shelves	5 Adjustable	5 Adjustable
Digital Display	Microprocessor	Microprocessor
Castors	✓	✓
Interior/Exterior Cabinet Finish	Stainless Steel	Stainless Steel
Insulation	70 mm	70 mm
High/Low Temperature Alarm	✓	✓
Fan Forced Refrigeration System	✓	✓
Door Lock	✓	✓
Solid Door / Glass Door	✓	✓
Optional Equipment		
Door ajar alarm	✓	✓
Port entry	✓	✓
Remote alarm	✓	✓
Temp alert	✓	✓
Independent data logger	✓	✓
Chart recorder	✓	✓
Battery backup for controller	✓	✓
Additional shelves	✓	✓

*Refer to warranty sheet