

LKUv 1613

LED

MediLine



Gross/net capacity	152/143 litre
Ext. dimensions in mm (w/d/h)	597/615/820
Int. dimensions in mm (w/d/h)	440/435/670
Energy consumption in 365 days	369 kWh
Climate rating	SN-ST ¹
Refrigerant	R 600a
Airborne acoustical noise emissions	47 dB(A)
Connection Rating	1.0 A
Voltage	220-240 V~
Cooling system	forced-ir
Defrosting	automatic
Temperature range	+2°C to +8°C
Gradient *	5.1°C
Max. fluctuation **	4.9°C
Housing material/colour	steel/white
Door/lid material	insulated glazed door
Liner Material	moulded polystyrol white
Type of Control	electronic controller
Temperature display	external digital
Interior light	LED
Fault: warning signal	visual and audible
Interface	RS 485
volt-free alarm contact	yes
Evaporator Cover	yes
Adjustable Shelving	3
Shelf material	grid shelves plastic-coated
Shelf loading	45 kg
Handle	Ergonomic door handle
Lock	no
Self-closing door	yes
Door hinges	right, reversible
Insulation	40 mm
Gross/net weight	46 / 43 kg
EAN-Nr.	9005382193235

1 Climate Ratings: **SN** +10°C to +32°C **N** +16°C to +32°C **ST** +16°C to +38°C **T** +16°C to +43°C

* Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

** Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.

Subject to modification. Timestamp: 21.03.2018

LIEBHERR