

BenchMAX Specifications

Labels

Sensor type:

- On edge, no registration mark required

Label savings:

- Up to 2 meters (78.74 inches) per roll during set up

Type:

- Single, front & back, or wrap-around labels.
- Pressure sensitive, die-cut, roll-formatted, Fan Folded,
- Opaque, clear, translucent.

Thickness:

- Minimum 0.02mm (0.0007 inches)

Length:

- Greater than 25mm (0.98 inch)

Height:

- Minimum 10mm (0.39 inches)
- Maximum 230mm (9.05 inches)

Direction:

- Left Hand Leading Edge (Internal or externally wound)

Roll Diameter:

- Maximum 300mm (11.81 inches)

Roll Core Diameter:

- 38mm (1.49 inches) and 76mm (2.99 inches)



A family
owned
Australian
business

Container & Dimensions

Suitable for round containers

Container Diameter:

- Minimum 8mm (0.31 inches)
- Maximum 110mm (4.3 inches) standard
maximum 220mm (8.66 inches) with removable or extended handle

Construction:

- Anodized 6061 Aluminum
- Food grade Stainless steel shafts and bolts

Pack Dimensions:

- 61cm (24 inches) x 59cm (23.2 inches) x 44cm (17.3 inches)
- Weight 33kg (72.7lbs)

Removable handle:

- Works the same as the standard handle for containers up to 110mm (4.3inches), in diameter. Can be removed for larger containers that are pre-filled.

Extended handle:

- Will only label large containers from 110mm (4.3inches)- 220mm (8.66inches) in diameter (if needing to label empty).

