

PLUS1000BM

Electronic Bench Mounted Tap 6 Star 6lpm

SMARTEC PLUS Electronic Single Temperature Bench Mounted Tap - Mains and Battery Powered

Technical Information:

Material	Stainless Steel / Plastic Solenoid Valve
Inlet	15mm Flexible connection
Outlet	15mm Aerator
Working Pressures	50kpa - 500kpa
Max Working Temp.	50°C
Valve	6 Volts Solenoid (15mm connection)
Finish	Chrome Plated / Satin
Servicing	Low Maintenance
Warranty	2 Years*



PLUS1000B	SMARTEC PLUS Chrome Plated - Battery Powered
PLUS1000M	SMARTEC PLUS Chrome Plated - Mains Powered
PLUS1000SB	SMARTEC PLUS Satin Finish - Battery Powered
PLUS1000SM	SMARTEC PLUS Satin finish - Mains Powered
PLUS1000SBM	SMARTEC PLUS Satin finish - Battery and Mains Powered

Features:

- Laser sensor technology stops nuisance triggering and activates on all colored skin tones.
- Sensitivity easily adjustable without tools.
- Alternate Run time and hygiene flush options available upon request.
- Supplied with inlet strainer and low controller.
- IP rated control box enclosure houses the solenoid valve and waterproof connections.
- Hygiene flush programmed included to reduce risk associated with legionella

